SONY

BC-U2A

Two-channel simultaneous battery charger/AC adaptor for BP-U90/U60/U60T/U30 Lithium-ion battery

Overview

Charges two BP-U90/U60/U60T/U30 batteries

The BC-U2A battery charger can simultaneously charge two compact BP-U90, BP-U60 / 60T or BP-U30 Lithium-ion batteries at high speed

Built-in AC adaptor provides 12 V DC power output while charging one battery

The BC-U2A also has 12 V DC power output cable to power a camcorder directly, while charging one battery simultaneously.

Portable design for ease of use

The BC-U2A has a mass of 620 g (1 lb 6 oz) and dimensions (W x H x D) of 177 x 53.2 x 137 mm (7 x 8 1/8 x 5 1/2 inches).
NOTE: BC-U2A is compliant with safety standard IEC62368-1.

Specifications

General	
Power Requirements	AC100V～240V 50/60Hz
Power consumption	89W
DC supply	[36W] 12V / 3.0A
Charging Voltage	16.4V
Dimensions (W x H x D)	177x53.2x137 (mm)
Mass	620 (g) +DC out cable
Operating Temperature	[DC supply]-5 ℃～+45℃ [Charge] 0℃～+45℃

Approximate charge times	
BP-U90	190 minutes
BP-U60 / 60T	150 minutes
BP-U30	130 minutes

Supplied Accessories

Supplied Accessories	Instruction manual Warranty Paper DC out cable

Related products

PXW-FS7M2

4K Super 35mm Exmor CMOS sensor XDCAM camera with Variable ND Filter, E-Mount (Lever Lock), 4K/2K RAW and XAVC recording

PXW-FS5

Grab and Shoot with handheld Super 35

PXW-FS5M2

'Grab and shoot' Super35 handheld camcorder with stunning new creative look, 4K 120fps HFR and HDR, α Mount lens system, Variable ND Filter, 4K/2K RAW and XAVC recording

PXW-Z190

4K Handheld Camcorder with all-new 1/3-type 3CMOS with 4K 50p/60p* recording capability, 25x zoom lens and advanced Face Detection AF

MCX-500

Multi-Camera Live Producer

Gallery