VPL-VW270ES

4K SXRD Home Cinema Projector with 1,500 lumen brightness, HDR Compatible and 4K Motionflow™



Overview

Bring incredible 4K detail to your favourite movies

Imagine bringing the truly cinematic quality of 4K into your own home. Now you can make this a reality with our VPL-VW270ES Home Cinema projector.

The VPL-VW270ES produces true 4K resolution images with our native 4K (4096×2160) SXRD panels – that's over four times the quality of Full HD.

Designed for your home cinema room and living room, the VPL-VW270ES delivers stunning, detail-packed images and incredibly lifelike colour like never before. And with 1,500 lm brightness, you're guaranteed an exceptional picture.

Colour availability may vary by country

Features

Native 4K SXRD™ panel

Featured in Sony's digital cinema projectors, advanced SXRD (Silicon X-tal Reflective Display) panel technology delivers native 4K (4096 x 2160) resolution images, with more than four times the detail of Full HD. Fine details are wonderfully clear and natural, without jagged edges or visible pixels.

See richer, deeper blacks

Latest SXRD 4K panels deliver even better contrast, as well as native 4K resolution. SXRD projection offers rich, inky blacks, as well as clear cinematic motion and image smoothness. Improvements to the panel's reflective silicon layer now mean even better light control, for precisely reproduced shadows and blacks.

Super-resolution Reality Creation

Exclusive Reality Creation technology analyses images right down to the pixel level. It uses powerful pattern-matching algorithms developed over years of movie production to enhance image crispness without increasing digital picture noise. It also upscales existing full HD Blu-ray Disc™ and DVD movies to near 4K quality.

Colours come alive with TRILUMINOS™

Discover true-to life colours and tones. The VPL-VW270ES incorporates TRILUMINOS colour, reproducing more tones and textures than standard projectors. Hard-to-reproduce crimson reds, aqua blues, and emerald greens are displayed beautifully so landscapes and seascapes look more vivid. Faces look better, too, with faithfully reproduced skin tones.

HDR compatibility: every image comes to life

Get the most from today's UHD Blu-ray and streaming services with High Dynamic Range. HDR video offers an expanded brightness range that delivers more realistic, high-contrast images and brilliant colours. Compatible with both HDR10 and HLG (Hybrid Log-Gamma) formats. Sony's home cinema projectors reproduce colour and contrast that's faithful to the creator's intention.

HDMI 18 Gbps compatibility

With an increase in 4K HDR 60P content, the VPL-VW270ES is now HDMI 18 Gbps compatible for smoother expressions of gradations.

4K Motionflow™

The powerful video processor in the VPL-VW270ES offers Motionflow™ for smooth and clear motion even when viewing 4K content. Motionflow adds frames to reduce blur, while maintaining brightness, making it ideal for fast-moving sports content. Cinema purists can choose True Theatre mode to retain the original 24fps.

1,500 lumens for high brightness

Enjoy the action with up to 1,500 lumens brightness, generated by a 225W lamp, for vibrant images on screens.

Watch for longer with a 225W ultra high pressure lamp

Enjoy up to 6000 hours* of viewing time (in low mode) from a long-lasting lamp. This means fewer lamp swaps, simpler maintenance, and lower running costs.

*Approximate recommended period, in low mode.

Motorised zoom lens and wide lens shift

Installing this projector in your room is easy with a 2.06x motorised zoom with a wide lens shift range. Adjust the position of the projector up to 85% vertically and 31% horizontally to get just the right angle for your movies.

Select from nine calibrated picture modes

Quickly set the picture to what you're watching or playing. Select from nine calibrated picture modes, including two theatre film modes, cinema digital, reference, TV, photo, game, bright cinema, and bright TV. An advanced HSV (Hue Saturation Value) colour tuning tool gives you even more control.

Front-facing fan

As the fan is positioned at the front of the projector, you don't need to worry about wall space and clearance for air inhale/exhaust during installation. This helps maximise throw distance for bigger projected images.

Specifications

Display System	
Display System	4K SXRD panel, projection system
Display device	
Size of effective display area	0.74" x 3
Number of pixels	26,542,080 (4096 x 2160 x 3) pixels
Projection lens	
Focus	Powered
Zoom	Powered (Approx. x2.06)
Lens shift	Powered Vertical: +85% -80% Horizontal: +/-31%
Light source	
Light source	High-pressure mercury lamp, 225 W type
D	

Recommended lamp replacement time *1

Rocammended lamn



NECOHIHEHAEA (AIII
replacement time

6,000 H (Lamp mode: Low)

	2 n	

Light output

Light output	1,500 lm (Lamp mode: High) *2	2
218116 0 4 6 9 4 6	±,000 (111 (Earlip 1110 ac. 111811) 2	_

Colour light output

Colour light output	1,500 lm (Lamp mode: High) *2
	_,

Displayable scanning frequency

Horizontal	19 kHz to 72 kHz
Vertical	48 Hz to 92 Hz

Display resolution*3

Computer signal input	Maximum display resolution: 1920 x 1080 dots (HDMI Input only)
	480/60p, 576/50p, 720/60p, 720/50p, 1080/60 i, 1080/50 i, 1080/60p,1080/50p, 1080/24p, 3840



Video signal input	x 2160/24p, 3840 x 2160/25p, 3840 x
	2160/30p, 3840 x 2160/50p, 3840 x
	2160/60p, 4096 x 2160/24p, 4096 x
	2160/25p, 4096 x 2160/30p, 4096 x
	2160/50p, 4096 x 2160/60p

OSD language	
OSD language	18-languages (English, Dutch, French, Italian, German, Spanish, Portuguese, Turkish, Russian, Swedish, Norwegian, Japanese, Simplified Chinese, Traditional Chinese, Korean, Thai, Arabic, Polish)

INPUT OUTPUT (Co	omputer / Video / Control)
HDMI1/HDMI2*4	Digital (RGB/Y Pb/Cb Pr/Cr)
Trigger	Minijack, DC 12 V Max. 100 mA
Remote	RS-232C, D-sub 9-pin (male)
LAN	RJ45, 10Base-T/100BASE-TX
IRIN	Mini Jack
USB	DC 5 V, Max. 500 mA



Acoustic noise 26 dB*5

Operating temperature / Operating humidity

5°C to 35°C (41°F to 95°F) / 35% to 85% (no condensation)

Storage humidity

Storage temperature / -20°C to +60°C (-4°F to +140°F) / 10% to 90% (no condensation)

Power requirements

AC 100 V to 240 V, 4.0 A to 1.7 A, 50/60Hz

Power consumption	390 W
Standby	0.4 W (when "Remote Start" is set to "Off")
	1.0W (LAN) (when "Remote Start" is set to "On")



Networked Standby When a LAN terminal is not

connected, it becomes a low

power consumption mode (0.5 W)

Standby Mode / Networked Standby Mode Activated

Standby Mode/

Networked Standby

Mode Activated

After about 10 Minutes

3D

3D capability	Yes
3D emitter	Built-in RD emitter
3D glasses	TDG-BT500A (Optional) Please contact your Sony representative for specific models available in your region.

Dimensions $(W \times H \times D)$ (without protrusions)

Dimensions (W x H x D) 496 x 205 x 464 mm

(without protrusions) $19 \frac{1}{2} \times 8 \frac{3}{32} \times 18 \frac{1}{4}$ inches

Mass

Mass Approx. 14 kg/31 lb

Supplied accessories

RM-PJ28 Remote Commander (1)

Size AA (R6) Manganese Batteries

(2)

Supplied accessories

Lens Cap (1)

AC Power Cord (1)

Operating Instructions (CD-ROM)

(1)

Quick Reference Manual (1)

Optional accessories

TDG-BT500A (3D glasses)*

Optional accessories

*Please contact your Sony

representative for specific models

available in your region.

Replacement lamp

Replacement lamp

LMP-H220

Notes

The figures are expected

*1	maintenance time and not guaranteed. They will depend on the environment or how the projector is used.
*2	The values are estimate.
*3	Displayed image may be converted for some input signals.
*4	HDMI Input2 is compatible with HDCP 2.2.
*5	They will depend on the environment or how the projectors is used. When under normal environment.
Environmental notice for customers in the USA	Lamp in this product contains mercury. Disposal of these materials may be regulated due to environmental considerations. For disposal or recycling information, please contact your local authorities or see www.sony.com/mercury for additional information.

Gallery



© 2004 - 2024 Sony Corporation. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Features and specifications are subject to change without notice. The values for mass and dimension are approximate. All trademarks are the property of their respective owners.