

## AC-80MD

AC Adaptor for use with Printer,  
3D Camera and IP converter



### Overview

AC-80MD is the AC Adaptor for use with Sony's Printer, 3D Camera and IP converter.

It is compatible with the UP-D711MD Digital Graphic Printer and MCC-3000MT 3D Full HD Medical Video Camera.

Input: AC 100 - 240V, 1.0 - 0.5 Amp, 50/60 Hz

Output: DC 24V, 3.3 Amp max.

Weight: 350g (AC adaptor only)

### Specifications

#### Specifications

|                   |                            |
|-------------------|----------------------------|
| Power requirement | AC 100 V - 240 V, 50/60 Hz |
|-------------------|----------------------------|

|               |               |
|---------------|---------------|
| Input current | 1.0 A - 0.5 A |
|---------------|---------------|

|                |         |
|----------------|---------|
| Output voltage | DC 24 V |
|----------------|---------|

|                |           |
|----------------|-----------|
| Output current | 3.3 A Max |
|----------------|-----------|

|                       |                                 |
|-----------------------|---------------------------------|
| Operating temperature | 0 °C to 40 °C (32 °F to 104 °F) |
|-----------------------|---------------------------------|

|                                   |  |
|-----------------------------------|--|
| Operating humidity                | 20% to 80%   |
| Operating pressure                | 700 hPa to 1,060 hPa   |
| Storage and transport temperature | -20 °C to +60 °C (-4 °F to +140 °F)  |
| Storage and transport humidity    | 20% to 90%   |
| Storage and transport pressure    | 700 hPa to 1,060 hPa   |
| Dimensions                        | 63 × 30.5 × 140 mm (w/h/d) (2 1/2 × 1 1/4 × 5 5/8 inches) Not incl. projecting parts |
| Mass                              | 350 g (12 oz) (AC adaptor only)  |
| Accessories provided              | Instructions for Use (1)<br>Service Contact List (1)                                 |

## Medical Specifications

|   |          |
|---|----------|
| Protection against electric shock           | Class I  |
| Protection against harmful ingress of water | Ordinary |

|   |   |
|---|---|
| Degree of safety in the presence of a flammable anesthetic mixture with air | Not suitable for use in the presence of a flammable anesthetic mixture with air or with oxygen or nitrous oxide |
|---|---|

---

|                   |            |
|-------------------|------------|
| Mode of operation | Continuous |
|-------------------|------------|

---

## Gallery

