

## MKS-R1620

16 Button remote control panel



**NETWORKED LIVE**

### Overview

**The MKS-R series remote panel controls matrix cross points of both IP and SDI routers connected to NS-BUS system.**

### Features

#### **Multiple buttons and functionalities**

MKS-R1620 has 16 buttons with source and destination display switching for easy configuration of the remote panel. All the panel products support multiple functions such as Salvo, Chop, Protect, Lock, etc. User friendly web menu for configuration.

#### **Redundant network and power supply**

Redundant power supply by DC IN and PoE. Network redundancy supported by two network ports.

### Specifications

#### GENERAL

Power supply	37V, 57V (PoE), DC IN 12V
--------------	---------------------------

Current consumption	(PoE), 0.7A DC
---------------------	----------------

Dimensions (W x H x D)	440 x 43.6 x 90 mm (17 3/8 x 1 3/4 x 3 5/8 in)
------------------------	--

Mass	Approx. 1.3kg (2lb 14oz)
Temperature ranges	Operational temperature: +5°C~+40°C (+41°F to +104°F) Storage temperature: -20°C~+60°C (-4°F to +140°F)
LAN	RJ-45 (×2) (PoE x1) 1000BASE-T

## Related products



### **PWS-110NM1**

IP Live System Manager Station



### **MKS-R3210**

32 Button remote control panel



### **MKS-R1630**

Remote control panel of NS-BUS system



### **MLS-X1**

Scalable and Reconfigurable Live Production Processor/Switcher



### **XVS-G1**

Powerful and Compact Live Production Switcher

## Gallery

