

AC-VQV10

V series battery AC adapter/charger



Overview

Power supply / charger compatible with P, H, and V series InfoLITHIUM batteries

High-speed dual charging of P, H, and V series InfoLITHIUM batteries.

Information display shows remaining amount and current battery levels in percentage.

Specifications

Basic Specs

| | |
|---------------------|--|
| Dimension (Approx.) | W 100 x H 67 x D 111 mm (4 x 2 3/4 x 4 3/8 inches) |
|---------------------|--|

| | |
|------------------|-----------------|
| Weight (Approx.) | 330 g (11.7 oz) |
|------------------|-----------------|

| | |
|-----------------------|----------------------------|
| Operating Temperature | 0 to +40°C (+32 to +104°F) |
|-----------------------|----------------------------|

| | |
|---------------------|-----------------------------|
| Storage Temperature | -20 to +60°C (-4 to +140°F) |
|---------------------|-----------------------------|

AC Power Requirements

| | |
|---------|-----------|
| Voltage | 100-240 V |
|---------|-----------|

| | |
|-----------|----------|
| Frequency | 50/60 Hz |
|-----------|----------|

Power Consumption

| | |
|-------------------|------|
| Power Consumption | 26 W |
|-------------------|------|

Adapter

| | |
|----------------------------------|----------------------|
| Output Voltage in Operating Mode | DC OUT 8.4 V / 1.7 A |
|----------------------------------|----------------------|

Charging Specs

| | |
|---------------------------------|---------------------------------------|
| Output Voltage in Charging Mode | Battery charge terminal 8.4 V / 2.2 A |
|---------------------------------|---------------------------------------|

| | |
|--------------|--------------|
| Quick Charge | Quick Charge |
|--------------|--------------|

| | |
|---------------------------|---|
| Intelligent Display (LCD) | Y |
|---------------------------|---|

| | |
|-----------|---|
| DC Charge | N |
|-----------|---|

Charging Time

| | |
|--|---------------------|
| NP-FH100 (Full Charge / Normal Charge) | 190 min. / 130 min. |
|--|---------------------|

| | |
|--|---------------------|
| NP-FH70 (Full Charge / Normal Charge) | 125 min. / 65 min. |
| NP-FH50 (Full Charge / Normal Charge) | 115 min. / 55 min. |
| NP-FP90 (Full Charge / Normal Charge) | 175 min. / 115 min. |
| NP-FP50 (Full Charge / Normal Charge) | 125 min. / 65 min. |
| NP-FP71 (Full Charge / Normal Charge) | 140 min. / 80 min. |
| NP-FV100 (Full Charge / Normal Charge) | 185 min. / 125 min. |
| NP-FV70 (Full Charge / Normal Charge) | 130 min. / 70 min. |
| NP-FV50 (Full Charge / Normal Charge) | 115 min. / 55 min. |

eco-info (It is indicated from the high order of priority)

| | |
|---|---|
| Reduction and phase-out of halogenated flame retardant (100%) | Halogenated flame retardants are not used in cabinets |
|---|---|

VOC-free vegetable oil based ink

VOC (Volatile Organic Compound)-free vegetable oil based ink is used for printing the cardboard

Remark

Remarks 1: Full Charge

Approximate minutes to charge an empty battery pack fully

Remarks 2: Normal Charge

Approximate minutes indicate the time when you charge normally

Gallery

