

BKM-229X

Analogue component input adaptor for LMD monitors



Overview Analogue component input adaptor for LMD monitors

Specifications

| Input | |
|----------------------|--|
| RGB, Component Input | BNC (x3) RGB: 0.7 Vp-p \pm 3 dB (Sync On Green, 0.3 Vp-p sync negative) Component: 0.7 Vp-p \pm 3 dB (75% chrominance standard color bar signal) |
| Audio Input | Phono jack (x2) (L, R), -5 dBu 47 kilohms or higher |
| External Sync Input | BNC (x1) 0.3 Vp-p to 4.0 Vp-p \pm bipolarity ternary or negative polarity binary |
| General | |

| | |
|--------------------------------------|---|
| Voltage | +3.3 V, +5 V DC (supplied from the main unit) |
| Power Consumption | Approx. 4.0 W |
| Operating Temperature | 0°C to 35°C (Recommended: 20°C to 30°C) 32°F to 95°F (Recommended: 68°F to 86°F) |
| Operating Humidity | 0% to 90% (no condensation) |
| Storage/Transport Temperature | -20°C to +60°C -4°F to +140°F |
| Storage/Transport Humidity | 0% to 90% |
| Operating/Storage/Transport Pressure | 700 hPa to 1060 hPa |
| Dimensions (W x H x D) *[1] | 100 x 20 x 162 mm 4 x 13/16 x 6 1/2 inches |
| Mass | Approx. 250 g Approx. 8.8 oz |
| Supplied Accessories | Operating Instructions (1) |

Notes

Note

*[1] The values for dimensions are approximate.

Gallery

