SONY

AC-300MD

Provides power for Sony LCD medical monitors



Overview The AC-300MD in an optional AC power adapter designed for use with Sony LCD medical monitors.

The adapter can operate wherever an AC mains outlet (100-240V, 50/60Hz) is available. It provides a regulated 26V DC output (max. 10.2 A) that's suitable for powering the monitors.

Specifications

ons	General	
	Power	AC IN: 100V –240V (50/60Hz) 3.1A DC OUT: 26V 10.2A
	Operating Temperature	0 °C to 40 °C (32 °F to 95 °F)
	Operating Humidity	30% to 85% (no condensation)
	Operating Pressure	700 hPa to 1060 hPa
	Storage/Transport Temperature	–20 °C to +60 °C (–4 °F to +140 °F)

SONY

Storage/Transport Humidity	20% to 90% (no condensation allowed)
Operating/Storage/Transport Pressure	700 hPa to 1060 hPa
Dimensions (W x H x D) *1	245 x 58 x 150 mm 9.6 x 2.3 x 5.9 in
Mass	1.5 kg 3 lb3 oz
Supplied Accessories	Instructions for Use(1) Service Contact List (1) AC power code (1) (supplied at local) * AC code connector C13 (1)
*1	The values for dimensions are approximate.

Related products

LMD-X2700MD

27-inch 4K 2D LCD medical monitor

LMD-X2705MD

27-inch 4K 2D LCD medical monitor with 3G-SDI

LMD-X310MD

31-inch 4K 2D LCD medical monitor

X310MT 31-inch 4K 3D/2D LCD medical monitor

LMD-



Gallery



© 2004 - 2024 Sony Corporation. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Features and specifications are subject to change without notice. The values for mass and dimension are approximate. All trademarks are the property of their respective owners.