

CBK-VF02

3.5" Colour LCD HD Viewfinder for PXW-X500



Overview

3.5" Colour LCD HD Viewfinder for cameras with a rectangle-type 26-pin viewfinder interface. The applicable cameras output the higher resolution QHD signal to this viewfinder. Camera operators can see the LCD, directly, because the optical loupe and the elbow parts can be flipped-up.

3.5" Colour LCD QHD Viewfinder Uses 26-pin viewfinder interface

Specifications

| to 17.0 V DC (supplied by the era) |
|------------------------------------|
| |
| 40C (32F to 104F) |
| to +60C (-4 F to +140 F) |
| ox. 680 g (1 lb 8.0 oz) |
| |



| External dimensions | 201mm (8 in) x 255mm (10 1/8 in) x 60mm (2 3/8 in) 89mm (3 5/8 in) |
|--|--|
| 3.5-inch colour TFT transflective LCD Image display area dimensions | 76.8 × 43.2 mm (31/8 × 13/4 inches) (H/V, 16:9 aspect ratio) |
| | |
| Performance | |
| Brightness | 200 cd/m2 (typical) (when eyepiece is attached) |
| Resolution | 500 lines or more |
| Colour temperature | 6500 K (typical) |
| | |
| Connector | |
| Connector | Rectangular 26-pin connector |
| | |
| Supplied accessories | |
| Supplied accessories | Operation manual (1) |
| | |
| Optional accessories | |
| Optional accessories | Viewfinder Rotation Assembly : BKW-401 |



Compatible products

PXW-X500, PMW-500, HXC-D70 - Please note to attach the viewfinder to the PMW-500, the firmware version on the camcorder must be 1.10 or later. To attach the viewfinder to the HXC-D70, the firmware version on the camera must be 1.21 or later.

Compatible products

Notes Design and specifications are subject to change without notice.

SONY

Gallery

