


## CNA-2

Camera Control Network  
Adapter



## Specifications

### General

Power

requirements LAN1

PoE (IEEE802.3af

DC 37 V – 57 V

Type1 Class0

compliant):

CCU power supply  
(CCA):

DC 10.5 V – 30 V

EXT I/O (D-SUB):

DC 10.5 V – 17 V

DC 12V IN:

DC 11.4 V – 12.6 V

Power consumption

9 W (main unit only, DC 12V IN)

Operating temperature	5°C to 40°C (41°F to 104°F)
Storage temperature	-20°C to +60°C (-4°F to +140°F)
Mass	660 g (1 lb 7.3 oz)
External dimensions (w/h/d)	100 mm × 42 mm × 181 mm (4 inches × 1 11/16 inches × 7 1/4 inches)

## Control connectors

- USB connector
- High Speed USB (USB2.0) (1)
- CCU REMOTE connector
- 8-pin multi-connector, jack (1)
- AUX REMOTE connector
- 8-pin multi-connector, jack (1)
- DC output: 30 V, 6 W
- External I/O connector
- D-SUB 15-pin (1)
- Network connector RJ-45 (2)
- 1000BASE-T: IEEE 802.3ab

## Accessories supplied

- Before Using This Unit (1)

## Accessories optional

### AC adaptor AC-UES1230M T

#### Related products



#### HDC-3500

Three 2/3-inch 4K CMOS sensors portable system camera for fibre operation



#### HDC-5500

High performance three 2/3-inch 4K CMOS sensor portable system camera with direct 4K output



#### HDC-P50

4K/HD compact POV system camera



#### HDC-P31

HD compact POV system camera with enhanced remote features and advanced HDR workflows



#### HDCU-5500

IP-ready Camera Control Unit (CCU) for HDC-5500 4K/HD system camera



#### HDCU-5000

Camera Control Unit (CCU) for HDC-5500 and HDC-3500/3100 series system cameras



#### HDCU-3500

IP-ready Camera Control Unit (CCU) for HDC-3500 4K/HD system camera



#### RCP-3500

Remote-control panel for HDC/HSC/HXC series cameras



#### RCP-3100

Joystick type of remote control panel for HDC/HSC/HXC series cameras. 5 units in 19-inch EIA rack.



#### MSU-3000

Master setup unit, multi camera remote control panel for system cameras (horizontal type)



#### MSU-3500

Master setup unit, multi camera remote control panel for system cameras (vertical type)

## Gallery

