SONY

UNI-OPL7C3

Outdoor Pressurized dome camera housing



Overview

Applicable Camera Models;
- SNC-RX550P - SNC-RX530P - SNC-RX570P Fixing Method;
-SNCA-WM20G (wall) -SNCA-CEILING (ceiling) -SNCA-WM20FC (see note) Rating;
-IP67 Operating Temperature;
--29°C to +50°C (SNCA-HEATER) Voltage;
-24 volts AC Optional accessories;
-SNCA-CLEAR/2 (included)
-SNCA-TINTED/2

Related products



SNC-EB600

Box-type 720p/30 fps Camera Powered by IPELA ENGINE EX™ - E Series



SNC-EB600B

Basic Box-type 720p/30 fps Camera Powered by IPELA ENGINE EX™ - E Series



SNC-EB630

Box-type 1080p/30 fps Camera Powered by IPELA ENGINE EX™ - E Series



SNC-EB630B

Basic Box-type 1080p/30 fps Camera Powered by IPELA ENGINE EX™ - E Series



SNC-VB600

Box-type 720p/60 fps Camera Powered by IPELA ENGINE EX™ - V Series



SNC-EP521

Standard Definition (PAL) PTZ Network Camera



SNC-EP580

1080p/30 fps PTZ Camera - E Series



SNC-ER521

Standard Definition (PAL) Rapid Dome Network Camera



SNC-ER550

720p/30 fps Rapid Dome Camera - E Series



SNC-ER580

1080p/30 fps Rapid Dome Camera - E Series

Gallery



© 2004 - 2026 Sony Corporation. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Features and specifications are subject to change without notice. The values for mass and dimension are approximate. All trademarks are the property of their respective owners.

Export PDF : November 22 2026