

### AC-80MD

AC Adaptor for use with Printer, 3D Camera and IP converter



#### Overview

AC-80MD is the AC Adaptor for use with Sony's Printer, 3D Camera and IP converter.

It is compatible with the UP-D711MD Digital Graphic Printer and MCC-3000MT 3D Full HD Medical Video Camera.

Input: AC 100 - 240V, 1.0 - 0.5 Amp, 50/60 Hz

Output: DC 24V, 3.3 Amp max. Weight: 350g (AC adaptor only)

### Specifications

Specifications	
Power requirement	AC 100 V - 240 V, 50/60 Hz
Input current	1.0 A - 0.5 A
Output voltage	DC 24 V
Output current	3.3 A Max
Operating temperature	0°C to 40°C (32°F to 104°F)

# SONY

Operating humidity	20% to 80%
Operating pressure	700 hPa to 1,060 hPa
Storage and transport temperature	–20 °C to +60 °C (–4 °F to +140 °F)
Storage and transport humidity	20% to 90%
Storage and transport pressure	700 hPa to 1,060 hPa
Dimensions	$63 \times 30.5 \times 140$ mm (w/h/d) (2 1/2 $\times$ 1 1/4 $\times$ 5 5/8 inches) Not incl. projecting parts
Mass	350 g (12 oz) (AC adaptor only)
Accessories provided	Instructions for Use (1) Service Contact List (1)

Medical Specifications	
Protection against electric shock	Class I
Protection against harmful ingress of water	Ordinary

## SONY

Degree of safety in the	Not suitable for use in the
presence of a	presence of a flammable
flammable anesthetic	anesthetic mixture with air or with
mixture with air	oxygen or nitrous oxide
Mode of operation	Continuous

### SONY

#### Gallery

