

## OTM-10GSR1

10GBASE-SR SFP+ Transceiver  
for Sony Networked Media  
Interface products



**NETWORKED LIVE**

### Overview

The OTM-10GSR1 SFP+ Ethernet transceiver supports multi-mode optical fibre for up to 300m.

### Specifications

#### General specifications

Power requirements 3.3 V DC

Power consumption 1 W

Dimensions 13.9 × 13 × 56.4 mm (9/16 × 17/32 × 2 1/4 in.) (width / height / depth)

Mass 21 g (0.74 oz.)

Temperature ranges  
Operating temperature: 5 °C to 40 °C (41 °F to 104 °F)  
Storage temperature: -20 °C to +60 °C (-4 °F to +140 °F)

## I/O specifications

Optical I/O Connector

Connector: LC Duplex optical connector  
 Signal formats: IEEE802.3ae 10GBASE-SR  
 Signal transmission speed: 10.3125 Gbps  
 Media Type: Multi Mode

Host interface

Connector: Card edge connector  
 Signal formats: SFF Committee SFF-8431 Specifications

## Related products



### PWS-100NM1

IP Live System Manager workstation



### NXLK-IP40F

SDI-IP converter board with 3G-SDI and SFP+ ports



### NXL-FR316

SDI-IP signal processing unit



### NXLK-IP45F

AV Multiplexer/Demultiplexer Board



### PWS-110NM1

IP Live System Manager Station



### PWSK-4506F

Networked Media Interface Board for PWS-4500 Live Server

## Gallery

