

ECM-166BMP

Uni-directional lavalier Electret condenser microphone



Overview

Black coloured uni-directional electret condenser lavalier microphone supplied with a 3-pole locking mini-plug for use with the bodypack transmitter included in UWP series

- Uni-directional, electret condenser microphone
- Reasonably priced lavalier microphone, ideal for ENG and EFP uses

Specifications

Audio Section

| | |
|-----------------------|-------------------------------------|
| Capsule Type | Electret Condenser |
| Frequency Response | 100 Hz to 10 kHz |
| Directivity | Uni-directional |
| Sensitivity *[1] | -45 dB (5.6 mV) \pm 3 dB |
| Output Impedance *[2] | 2.5k Ω \pm 30%, Unbalanced |
| Dynamic Range | 96 dB or more |

| | |
|-------------------------------|---------------|
| Signal-to-Noise Ratio *[3] | 60 dB or more |
|-------------------------------|---------------|

| | |
|---------------------|-------------------|
| Inherent Noise *[4] | 34 dB SPL or less |
|---------------------|-------------------|

| | |
|---|------------|
| Maximum Input Sound Pressure Level *[5] | 130 dB SPL |
|---|------------|

General Section

| | |
|-----------|--|
| Connector | BMP type. Supplied with ø3.5 mm, 3-pole mini plug. |
|-----------|--|

| | |
|-----------|-------------------|
| Mic Cable | 3.9 feet 1.2 m |
|-----------|-------------------|

| | |
|--------------------|-------------------|
| Power Requirements | DC 1.1 V to 10.0V |
|--------------------|-------------------|

| | |
|-------------------|----------------|
| Power Consumption | 0.4 mA or less |
|-------------------|----------------|

| | |
|-----------------|--|
| Dimensions *[6] | φ12.7 X 23.8 mm (Mic head) φ1/2 X 15/16 inches (Mic head) |
|-----------------|--|

| | |
|------|----------------------------------|
| Mass | Approx. 19.8 g Approx. 0.7 oz |
|------|----------------------------------|

| | |
|----------------------|---|
| Supplied Accessories | Urethane type windscreen (1) Single/horizontal type tie clip (1) Operating instructions (1) |
|----------------------|---|

Notes

Note

- *[1] 0 dB = 1 V/Pa, at 1 kHz
 - *[2] Output impedance at 1 kHz
 - *[3] A-weighted, 1 kHz, 1 Pa.
 - *[4] 0dB SPL = 20? Pa.
 - *[5] 0 dB SPL = 20? Pa.
 - *[6] The values for dimensions are approximate.
-

Related products



UWP-D11

UWP-D bodypack wireless microphone package



UWP-D12

UWP-D handheld wireless microphone package



UWP-D16

UWP-D bodypack and XLR plug-on wireless microphone package

Gallery

