SONY

MKS-E1620

16 Rotary Encoder Remote Control Panel



NETWORKED LIVE

Overview

The MKS-E1620 remote control panel simplifies operation of Sony's Live Element Orchestrator in live production applications.

Supporting fast, accurate operation in live environments, the hardware control panel features 16 encoders that can adjust various parameters of live equipment such as HDR colors and contrast for compatible Sony camera systems.

Specifications


General	
Power supply	37V, 57V (PoE), DC IN 12V
Current consumption	0.3A, 0.2A (PoE), 0.7A DC
Dimensions (W x H x D)	440 x 43.6 x 90 mm (17 3/8 x 1 3/4 x 3 5/8 in)
Mass	Approx. 1.5kg (3 lb 4.9 oz)
Temperature ranges	Operational temperature: 5°C to 40°C (41°F to 104°F) Storage temperature: -20°C to +60°C (-4°F to +140°F)

Information on EU Data Act: Click here to check if your Sony product and/or related service is subject to the EU Data Act.

Gallery







© 2004 - 2026 Sony Corporation. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Features and specifications are subject to change without notice. The values for mass and dimension are approximate. All trademarks are the property of their respective owners.

Export PDF : November 19 2026