

AC-VQ1051

L series battery AC adapter/charger



Overview

AC Adaptor / Charger compatible with L series InfoLITHIUM™ batteries

- Recharging time (Normal / Full charge): F570 110 min / 170 min; F770 185 min / 245 min; F970 285 min / 345 min
- Intelligent display confirms charging time left and remaining battery life in minutes and as percentage
- Relay type recharges up to two batteries simultaneously

Specifications

Basic Specs

| | |
|-----------------------|-------------------------------------------------------|
| Dimension (Approx.) | W 123 x H 53 x D 135mm (4 7/8 x 2 1/8 x 5 3/8 inches) |
| Weight (Approx.) | 400g (14.1oz) |
| Operating Temperature | +0 to +40°C (+32 to +104°F) |
| Storage Temperature | -20 to +60°C (-4 to +140°F) |

AC Power Requirements

| | |
|---------|----------|
| Voltage | 100-240V |
|---------|----------|

| | |
|-----------|---------|
| Frequency | 50/60Hz |
|-----------|---------|

DC Power Requirements

| | |
|---------|--------|
| Voltage | 12/24V |
|---------|--------|

Power Consumption

| | |
|-------------------|--------------------------------------|
| Power Consumption | 33-43VA (BATT), 40-53VA (VCR/CAMERA) |
|-------------------|--------------------------------------|

Adapter

| | |
|----------------------------------|---------------|
| Output Voltage in Operating Mode | DC8.4V / 2.0A |
|----------------------------------|---------------|

Charging Specs

| | |
|---------------------------------|---------------|
| Output Voltage in Charging Mode | DC8.4V / 1.6A |
|---------------------------------|---------------|

| | |
|--------------|--------------|
| Quick Charge | Quick Charge |
|--------------|--------------|

| | |
|---------------------------|---|
| Intelligent Display (LCD) | Y |
|---------------------------|---|

| | |
|-----------|---|
| DC Charge | Y |
|-----------|---|

Charging Time

NP-F970 (Full Charge /
Normal Charge) 345 min / 285 min

NP-F960 (Full Charge /
Normal Charge) 295 min / 235 min

NP-F950 (Full Charge /
Normal Charge) 260 min / 200 min

NP-F930 (Full Charge /
Normal Charge) 245 min / 185 min

NP-F770 (Full Charge /
Normal Charge) 245 min / 185 min

NP-F750 (Full Charge /
Normal Charge) 205 min / 145 min

NP-F730 (Full Charge /
Normal Charge) 195 min / 135 min

NP-F730H (Full Charge
/ Normal Charge) 205 min / 145 min

NP-F570 (Full Charge /
Normal Charge) 170 min / 110 min

NP-F550 (Full Charge /
Normal Charge) 145 min / 85 min

NP-F530 (Full Charge /

Normal Charge) 140 min / 80 min

NP-F330 (Full Charge /
Normal Charge) 115 min / 55 min

Eco-info (It is indicated from the high order of
priority)

Use of lead-free solder (use 100% in weight) Lead-free solder is used for soldering

Reduction and phase-out of halogenated flame retardant (100%) Halogenated flame retardants are not used in cabinets and in printed wiring boards

Gallery

