

AC-DN10A

AC Adapter/Charger



Overview

- Compact and lightweight AC adaptor/charger
- Maximum 100 W DC power supply
- V-mount mechanism for direct attachment to compatible camcorders
- XLR-4-pin output to power other equipment

Specifications

General

Power requirements 100-240 V AC, 50/60 Hz

Power consumption 130 VA or lower

Operating temperature 0 °C to 35 °C
(32 °F to 95 °F)

Mass Approx. 810 g (1 lb 14 oz)

Dimensions (width / height / depth) 101 x 177 x 48 mm
(4 x 7 x 1 15/16 inches)

Output

Output power (DC)	100 W (max.)
Output voltage (DC)	16.7 V
Output current (DC)	6 A (max.) However, for temperatures in the range 35 °C to 45 °C (95 °F to 113 °F), the maximum output current is as follows. Up to 40 °C (104 °F): 5 A (max.) Up to 45 °C (113 °F): 4 A (max.)
Output terminal (DC)	Square 5-pin connector
XLR 4-pin connector	16.7 V, 6 A (max.)
Output terminal (DC)	Square 5-pin connector 16.8 V, 5 A/3 A 14.2 V, 5.7 A

Supplied accessories

Operating Instructions (1)
Optional accessory
DC power cord

Gallery

