
## Multi-Touch Overlay Kit (STP-IR100 Series)

Multi-touch overlay kit for 55", 65", 75" and 85" 4K Professional Displays



#### Overview

#### Effortless screen interaction at your fingertips

Available to match screen sizes from 55" up to 85" these slim and light, easy-to-fit overlay kits transform 4K Professional Displays into a multi-touch enabled interactive screen.

Interact with the display using your finger, pen or other opaque object. Precision IR technology ensures a smooth, accurate and highly responsive user experience with up to ten touch points (depending on application support).

The overlay's clean, simple design features a slim bezel that blends discreetly into any environment, while fingerprint resistant glass minimises unsightly smears and marks.

Our touch-enabled 4K Professional Displays\* are ideal for a wide range of interactive signage and information kiosk applications – from schools, universities, museums, libraries, boardrooms and offices to hotel lobbies, hospitality zones, retail stores and visitor attractions.

Multi-touch overlay kit is supplied by Assist Co. Ltd.

STP-55IR100 overlay kit compatible with 55-inch Professional Displays

STP-65IR100 overlay kit compatible with 65-inch Professional Displays



STP-75IR100 overlay kit compatible with 75-inch Professional Displays

STP-85IR100 overlay kit compatible with 85-inch Professional Displays

\*Professional Display available separately

#### **Features**

#### Engage audiences with a touch

Responsive, high quality touchscreen overlays transform your Professional Display (available separately) into a super-size touch enabled interactive terminal.

#### Responsive, accurate multi-touch performance

Audience engagement is right at your fingertips. Customers and visitors can't keep their hands off these big, beautiful screens: up to 10 multi-touch points (depends on application) ensure accurate, responsive performance across the entire display area.

#### Range of screen size options

There's a choice of multi-touch overlays, offering guaranteed compatibility with current Professional Display models in screen sizes from 55" up to 85".

#### Easy installation and set up

Deploy your multi-touch display solution in minutes. Overlay kit is powered directly by USB connection.

### Specifications

Touch	
Touch type	IR (Infrared Rays) Spread
Input Method	Finger, Pen and Opaque objects
Available object size	Single touch 6 mm, Multi touch 8

fortouch	mm
Response Time	< 15ms
Frame Rate	125 Hz
Touch Accuracy	±2 mm (over 90% Area)
Interface	USB 2.0
Protection Glass Thickness	STP-55IR100 - 2.8 mm STP-65IR100 - 2.8 mm STP-75IR100 - 3.2 mm STP-85IR100 - 4 mm
Protection Glass Transmission	< 85%
Operating System Support	Windows 7 / 8 / 8.1 / 10 / Mac OS X (10.6 or later) / Android (Kernel 4.0 or later) / Linux (Kernel 3.5 or later) / Chrome
Multi touch point	Max 10 Point
Touch Resolution	32767 × 32767
Connectivity	
Input	USB
Average Current	< 300mA



Working Voltage	DC 5V $\pm$ 5%
-----------------	----------------

Physical Specification		
Colour	Black	
Bezel Width	STP-55IR100 - 19 mm STP-65IR100 - 19 mm STP-75IR100 - 20.5 mm STP-85IR100 - 25.1 mm	
Overlay Dimension (W x H x D)	STP-55IR100 - 1252.8 × 723.4 × 31 mm STP-65IR100 - 1471.5 × 846.5 × 31 mm STP-75IR100 - 1696.2 × 974.3 × 34.1 mm STP-85IR100 - 1927.2 × 1108.2 × 28.5 mm	
Weight (Head)	STP-55IR100 - 9.1 Kg STP-65IR100 - 11.6 Kg STP-75IR100 - 16.2 Kg STP-85IR100 - 24.6 Kg	
Carton Dimensions (W x H x D)	STP-55IR100 - 1366 × 815 × 140 mm STP-65IR100 - 1585 × 940 × 140 mm STP-75IR100 - 1808 × 1066 × 140	

	mm STP-85IR100 - 2040 × 1200 × 140 mm
Packed Weight	STP-55IR100 - 14.9 Kg STP-65IR100 - 18.8 Kg STP-75IR100 - 24.5 Kg STP-85IR100 - 34.3 Kg
Special Features	
Language (Manual)	Arabic, Chinese, English, French,Japan, Spanish, Russian, Vietnamese
Environmental Co	nditions
Environmental Co Operation Temperature	nditions 0°C ~ 40°C
Operation Temperature	
Operation Temperature	0 °C ∼ 40 °C
Operation Temperature	0 °C ∼ 40 °C
Operation Temperature Operation Humidity	0 °C ∼ 40 °C
Operation Temperature Operation Humidity Certification	$0 ^{\circ}\text{C} \sim 40 ^{\circ}\text{C}$ $20 ^{\circ}\text{W} \sim 80 ^{\circ}\text{W}$ $FCC / \text{CB} / \text{RCM} / \text{EAC} / \text{GB} / \text{ICES} / \text{CB} /$

Install Accessories / User Manual

### Gallery

