

ECM-678

Shotgun Electret condenser microphone



Overview

For superior sound quality, choose the ECM-678. It delivers superior sensitivity of -28 dB (0dB=1V/Pa) and extremely low inherent noise of less than 16 dB SPL. This microphone balances the need for a compact size with its ability to deliver excellent performance. The result is a highly directional microphone that is only 250 mm in length.

Specifications

Audio Section

Capsule Type	Mono Electret Condenser
Frequency Response	40 Hz to 20 kHz
Directivity	Uni-directional (super-cardioid)
Sensitivity *[1]	-28 dB +/- 3 dB
Output Impedance * [2]	200Ω ± 20%, Balanced
Dynamic Range	111 dB or more

Signal-to-Noise Ratio 78 dB or more
*[3]

Inherent Noise *[4] 16 dB SPL or less

Induction Noise From
External Magnetic 0 dB SPL or less
Field *[5]

Wind Noise *[6] 60 dB SPL or less (without screen)

Maximum Input
Sound Pressure Level 127 dB SPL
*[7]

General Section

Connector XLR-3-12C (male)

Mic Cable XLR-3 to XLR-3
480 mm
18.9 inches

Power Requirements External, DC 48 V +/-4 V

Dimensions *[8] $\phi 20 \times 250$ mm
 $\phi 13/16 \times 9 \ 7/8$ inches

Mass Approx. 7 oz
Approx. 200 g

Windscreen (1)

Supplied Accessories	Stand adaptor (2) Short LR cable (for camcorder use) (1) Operating instructions (1) Mic spacer (2) Mic holder (1) Carrying case (1)
----------------------	--

Notes

Note	*[1] 0 dB = 1 V/Pa, at 1 kHz *[2] Output impedance at 1 kHz *[3] A-weighted, 1 kHz, 1 Pa. *[4] 0 dB SPL = 20 μ Pa. *[5] dB SPL/1E-7 T, 0 dB SPL = 20 μ Pa. *[6] Wind noise at 2m/s (0 dB SPL = 20 μ Pa.) *[7] 0 dB SPL = 20 μ Pa. *[8] The values for dimensions are approximate.
------	--

Related products



HXC-FB80
Three 2/3-inch
Exmor™ CMOS sensor
HD colour studio

camera

Gallery

