

## F-115B

Dynamic microphone ideal for adverse weather conditions



### Overview

\* Ideal for sound pick-up, especially under adverse weather conditions such as rain or heavy wind thanks to its water-shedding, double-layered windscreen

\* A special rubber at the core of the microphone reduces shocks and vibrations

\* Directly connected microphone cable is water-resistant - limiting deterioration of internal parts

\* XLR-3-12C type connector

\* Frequency response: 40 Hz to 12 kHz

\* Dimensions: 62 dia. x 203 mm (2 1/2 dia. x 8 inches)

\* Mass: approx. 330 g (11.6 oz)

### Specifications

#### Audio Section

Capsule Type	Dynamic
Frequency Response	40 Hz to 12 kHz
Directivity	Omni-Directional
Sensitivity *[1]	-54 dB +/- 2dB

Output Impedance * [2]	400Ω±20%, Balanced
---------------------------	--------------------

Induction Noise From External Magnetic Field *[3]	5 dB SPL or less
---	------------------

Wind Noise *[4]	Less than 40 dB SPL
-----------------	---------------------

## General Section

Connector	XLR-3-12C (male)
-----------	------------------

Mic Cable	9.8 feet 3 m
-----------	-----------------

Power Requirements	No power required
--------------------	-------------------

Dimensions *[5]	φ62 mm x 203 mm φ2 1/2 x 8 inches
-----------------	--------------------------------------

Mass	Approx. 330 g Approx. 11.5 oz
------	----------------------------------

Supplied Accessories	Operating instructions (1)
----------------------	----------------------------

## Notes

\*[1] 0 dB = 1 V/Pa, at 1 kHz

\*[2] Output impedance at 1 kHz

\*[3] dB SPL/1E-7 T, 0 dB SPL = 20?

Note

Pa.

\*[4] Wind noise at 2m/s (0 dB SPL = 20 Pa.)

\*[5] The values for dimensions are approximate.

---

## Gallery

