

## ECM-44BMP

Affordable omni-directional lapel microphone



### Overview

Sony has produced over five million professional ECM (Electret Condenser Microphones) microphones and the ECM-44 is the affordable, general voice model. It provides good sound quality and is widely used in business presentation systems and TV production. The ECM-44 is available in four versions, featuring different connector types. This model, ECM-44BMP, has a 3.5mm locking jack for use with the UWP and UWP-D bodypack transmitters (excluding UTXB03HR).

#### **Convenient to use**

The ECM-44 is an affordable alternative to the traditional hand held microphone and being 'hands free' it allows the presenter to concentrate on her/his performance

#### **Professional image**

Either 'in front of camera' or at a business presentation the ECM-44 creates a professional and tidy image.

#### **Easy to use**

It can often be difficult to achieve good quality voice pick-up but the ECM-44 can help get good results. The microphone's capsule is designed for general voice pick-up with a mid-frequency emphasis characteristic and a suitable frequency response.

## Features

### Tuned for voice pick-up

The ECM-44's capsule features an emphasis curve and a suitable frequency response for voice pick-up.

### Compact size

The capsule has a diameter of only 8.5mm and is 14.5mm long.

### Ready for wireless systems

The ECM-44BMP is compatible with the Sony UWP and UWP-D bodypack transmitters.

## Specifications

### Audio Section

Capsule Type	Electret Condenser
Frequency Response	40 Hz to 15 kHz
Directivity	Omni-directional
Sensitivity *[1]	-40.0 dB (10 mV)
Output Impedance *[2]	2.5kΩ±30%, Unbalanced
Dynamic Range	90 dB or more
Signal-to-Noise Ratio *[3]	62 dB or more
Inherent Noise *[4]	32 dB SPL or less
Induction Noise From External Magnetic Field *[5]	5 dB SPL or less

Wind Noise *[6]	40 dB SPL or less (with windscreen)
-----------------	-------------------------------------

Maximum Input Sound Pressure Level *[7]	122 dB SPL
---	------------

## General Section

Connector	BMP type. Supplied with ø3.5 mm, 3-pole mini plug.
-----------	--

Mic Cable	3.9 feet 1.2 m
-----------	-------------------

Power Requirements	DC 1.1 V to 10.0V
--------------------	-------------------

Power Consumption	0.4 mA or less
-------------------	----------------

Dimensions *[8]	ø8.5 x 14.5 mm (Mic head) ø11/32 x 19/32 inches (Mic head)
-----------------	---

Mass	Approx. 18 g Approx. 0.6 oz
------	--------------------------------

Supplied Accessories	Urethane type windscreen (1) Single/horizontal type tie clip (1) Operating instructions (1) Mic case (1)
----------------------	---

Optional Accessories	Wind screen pack Horizontal single-clip pack
----------------------	---

## Notes

### Note

- \*[1] 0 dB = 1 V/Pa, at 1 kHz
- \*[2] Output impedance at 1 kHz
- \*[3] A-weighted, 1 kHz, 1 Pa.
- \*[4] 0 dB SPL = 20  $\mu$ Pa.
- \*[5] dB SPL/1E-7 T, 0 dB SPL = 20  $\mu$ Pa.
- \*[6] Wind noise at 2m/s (0 dB SPL = 20  $\mu$ Pa.)
- \*[7] 0 dB SPL = 20  $\mu$ Pa.
- \*[8] The values for dimensions are approximate.

## Related products



### UWP-D21

UWP-D bodypack wireless microphone package



### UWP-D22

UWP-D handheld wireless microphone package



### UWP-D26

UWP-D bodypack transmitter and XLR plug-on wireless microphone transmitter package

## Gallery

