

HVO-550MD

HD Medical Video Recorder,
DVD/USB/NAS



Overview

Save time with simultaneous HD video recording to internal and external media or network sharing. Compatible with a wide range of modalities and external command accessories.

From patient records to education, training and referral to other physicians, modern medical workflows benefit from the increased convenience and detail offered by HD video recording.

The HVO-550MD Medical Digital Network Recorder has been designed for use in a wide range of clinical environments, including hospital radiology and operating rooms, surgical centres and doctors' offices.

Suitable for storing High Definition videos from ultrasound, digital X-ray, endoscopic, laparoscopic and other compatible diagnostic and surgical imaging systems, the recorder offers extensive connection options with a wide range of current and legacy devices.

The HVO-550MD stores HD or Standard Definition video on its high-capacity internal hard disk drive. Via simple menu selection, video can be recorded at the same time to an external USB drive or network server, or burned directly to the recorder's internal DVD drive. This simultaneous recording capability saves time,

eliminating the need to export or copy video files to another storage medium after recording. It also provides an extra safeguard against the risk of losing valuable data.

The recorder is the ideal replacement for the DVO-1000MD. Sharing the same command set for control via RS-232C or USB, it offers a smooth migration to a hard -disk-based HD workflow.

Features

High Definition video recording

Recording crisply-detailed HD video at up to 720p, the HVO-550MD offers an improvement in image quality over Standard Definition recording devices such as the DVO-1000MD.

Simultaneous recording on internal HDD and external media

To minimise the risks of accidental data loss, video files can be recorded onto the internal hard disk drive simultaneously with a DVD, a connected USB drive or a network server. This also helps to shorten workflow, since videos do not need to be exported or copied onto another device after being recorded onto the internal HDD.

Burn files to DVD

Video files can be burned permanently onto the recorder's internal optical disc drive (DVD-R) for convenient storage and longer-term archive.

Compatible with DVO-1000MD commands

The HVO-550MD shares the same command set as the Sony DVO-1000MD DVD recorder. This simplifies migration from the DVO-1000MD to benefit from HD recording as well as HDD-based workflows.

Wide range of interfaces and network data transmission

The HVO-550MD is compatible with a wide range of modalities, including current HD as well legacy SD devices. Interfaces are provided for HDMI, DVI, composite video, S-Video and audio, as well as networked data transmission through CIFS to a centralised server.

Long recording time, even in HD at best image quality settings

The recorder's high-capacity disk drive allows long video recordings without interruption, even in High Definition. A choice of three Image Quality settings (Standard/High/Best) permits between 60 and 194 hours of HD video recording (or between 158 and 348 hours of SD video). Each individual recording can be up to 24 hours long. Videos can be exported as either high quality AVCHD or PC-friendly MP4 files.

Compliance with Medical Safety Standards

The recorder is compliant with and certified for IEC 60601-1 and product safety standards in the U.S.A., Canada and Europe. Registration status as a medical device may vary, depending on country.

For more details, please contact your nearest Sony office or an authorised dealer.

Pre-recording function

The preceding 5 seconds of video is continuously captured before the start of recording is triggered, ensuring that important moments aren't lost.

Specifications

Recording Features

Recording Video Format	MPEG-4 AVC/H.264
------------------------	------------------

Recording Audio Format	AC-3/AAC LC
Recording File Format	AVCHD/MP4
Recording Media	Internal HDD (500GB), DVD-R, External USB Storage, Network (CIFS)
Recording Resolution	1280 × 720/59.94p, 1280 × 720/50p, 720 × 480/59.94i, 720 × 576/50i
Recording Bit Rate (HD)	14Mbps (Best), 8Mbps (High), 4Mbps (Standard)
Recording Bit Rate (SD)	5Mbps (Best), 3Mbps (High), 2Mbps (Standard)
3D Recording	-

Connectors

Input Connectors	HDMI (Type A) (1), DVI-D (DVI 19-pin) (1), S VIDEO (Mini DIN 4-pin type) (1), VIDEO (BNC type) (1) AUDIO (Stereo mini jack) (1) DC IN (DIN 3-pin)
Output Connectors	HDMI (Type A) (1), DVI-D (DVI 19-pin) (1), S VIDEO (Mini DIN 4-pin

type) (1), VIDEO (BNC type) (1)
AUDIO (Stereo mini jack) (1)

Other Interfaces

USB (Type A) (3), USB (Type B) (1),
Network (RJ-45, 1000 Base-T/100
Base-TX) (1)), REMOTE RS-232C (D-
sub 9-pin) (1), REMOTE contact
switch (stereo mini jack) (2)
REMOTE MONITOR (RJ-45) (1),
Equipotential

General

Power Requirements

+12 V to +24 V DC (supply from AC-
81MD AC adaptor)

Input current

3.5 A to 1.8 A

Operating Temperature

5°C to 40°C (41°F to 104°F)

Operating Humidity

20% to 80% (Maximum wet-bulb
temperature: 30°C (86°F)) (no
condensation)

Operating Pressure

700 hPa to 1060 hPa

Storage and transport temperature

-20°C to +60°C (-4°F to +140°F)

20% to 90% (Maximum wet-bulb

Storage and transport humidity temperature: 30°C (86°F) (no condensation)

Storage and transport pressure 700 hPa to 1060 hPa

Mass 3.2 kg (7 lb. 0.88 oz.)

Dimensions (including longest protrusions) 212.0 × 287.7 × 105.5 mm (8 3/8 × 11 3/8 × 4 1/4 in.)

Supplied Items Before Using This Unit (1), CD-ROM (Instructions for Use, PROTOCOL MANUAL) (1), Warranty booklet (1), AC adapter (1), AC adapter Instructions for Use (1), Service Contact List (1)

Related products



MCC-500MD

Full HD surgical video camera with Exmor™ CMOS sensor.



MCC-1000MD

Two-piece Full HD surgical video camera

Gallery

