

MKS-R3210

32 Button remote control panel



NETWORKED LIVE

Overview

The MKS-R series remote panel controls matrix cross points of both IP and SDI routers connected to NS-BUS system.

Features

Multiple buttons and functionalities

MKS-R3210 has 32 buttons for source and destination switching for easy configuration of the remote panel. All the panel products support multiple functions such as Salvo, Chop, Protect, Lock, etc. User friendly web menu for configuration.

Redundant network and power supply

Redundant power supply by DC IN and PoE. Network redundancy supported by two network ports.

Specifications

General

Power supply	37V, 57V (PoE), DC IN 12V
--------------	---------------------------

Current consumption	(PoE), 0.7A DC
---------------------	----------------

Dimensions (W x H x D)	440 x 43.6 x 90 mm (17 3/8 x 1 3/4 x 3 5/8 in)
------------------------	--

Mass	Approx. 1.3kg (2lb 14oz)
Temperature ranges	Operational temperature: +5°C~+40°C (+41°F to +104°F) Storage temperature: -20°C~+60°C (-4°F to +140°F)
LAN	RJ-45 (× 2) (PoE x1) 1000BASE-T

Related products



PWS-110NM1
IP Live System Manager Station



MKS-R1620
16 Button remote control panel



MKS-R1630
Remote control panel of NS-BUS system



MLS-X1
Scalable and Reconfigurable Live Production Processor/Switcher



XVS-G1
Powerful and Compact Live Production Switcher

Gallery

