

MKS-R1630

Remote control panel of NS-BUS system



NETWORKED LIVE

Overview

The MKS-R series remote panel controls matrix cross points of both IP and SDI routers connected to NS-BUS system.

Features

Multiple buttons and functionalities

MKS-R1630 has 2 inch display for status indication, showing source, destination and levels, and used for easy configuration of the remote panel. All the panel products support multiple functions such as Salvo, Chop, Protect, Lock, etc. User friendly web menu for configuration.

Redundant network and power supply

Redundant power supply by DC IN and PoE.

Network redundancy supported by two network ports.

Specifications

General

| | |
|---------------------|--------------------------------------|
| Power supply | 37V, 57V (PoE), DC IN 12V |
| Current consumption | (PoE), 0.7A DC |
| | 440 x 43.6 x 90 mm (17 3/8 x 1 3/4 x |

Dimensions (W x H x D) 3 5/8 in)

Mass Approx. 1.3kg (2lb 14oz)

Temperature ranges Operational temperature:
+5°C~+40°C (+41°F to +104°F)
Storage temperature: -20°C~+60°C
(-4°F to +140°F)

LAN RJ-45 (×2) (PoE x1) 1000BASE-T

Related products



MKS- R3210

32 Button remote control panel



MKS- R1620

16 Button remote control panel



PWS- 110NM1

IP Live System Manager Station



PWS- 110RS1

Routing Control Station

Gallery

