

ZRA-R1

Optical receiver for Crystal LED
large display solutions



Overview

System configurations with greater connectivity and flexible set up

The ZRA-R1 converts the optical signal from ZRA-T1 and flawlessly connects to the ZRD series cabinet from up to 300 m away. Experience a more flexible way of integrating Crystal LEDs throughout more AV projects with this long distance receiver.

Specifications

Supported model

Cabinet	ZRD-B-series/C-series ZRD-BH-series/CH-series
---------	--

Controller	ZRCT-300
------------	----------

Type

Optical receiver

Interface

Input	SFP+ (multi-mode optical fiber)
-------	---------------------------------

Output	RJ45 x3
--------	---------

Transmission

Fiber optic	300m (maximum)
-------------	----------------

Support signal resolution

up to 1920x1080 (Full HD)
(4 pair required for 4K screen)

Dimensions

w x d x h (mm)	110 x 142.5 x 33.5 mm
----------------	-----------------------

Mass

(g)	610 g
-----	-------

Power *1

Requirement	DC 5V / 2A
-------------	------------

Consumption	10W
-------------	-----

Type of terminal	USB Type-C
------------------	------------

Operating Temperature

0°C - 45°C (32°F~113°F)

Storage Temperature

-20°C - 60°C (4°F~140°F)

Operating Humidity

20-80% (No condensation)

Storage Humidity

20-80% (No condensation)

Notes

*1

Please use a USB AC adapter that is USB PD compliant.
Operation is not guaranteed with all USB AC adapters.

Related
products



ZRA-T1

Optical transmitter for

Crystal LED large
display solutions

Gallery

