

#### Professional Disc

Single, Dual, Triple, and Quad layer Professional Disc



Overview

Ideal for archiving and deliveries

Outstanding recording capacity with up to 600 minutes of HD recording with the Quad layer version

Rugged and reliable HD media for day-to-day broadcasting

Designed for exceptional performance in tough conditions with advanced Hard Coat technology and a durable cartridge

PFD-23A: up to 85 minutes of XDCAM 4.2.2 PFD-50DLA: up to 1.5 hours of XDCAM 4.2.2 PFD-100TLA: over 3 hours of XDCAM 4.2.2 PFD-128QLW: up to 4 hours of XDCAM 4.2.2

**Proven Technology since 2003** 

**Optimized Cost per GB** 

**Free Customer Service** 

Compatibility: always check the compatibility of your equipment prior to any purchase

Specifications

Format

| Storage Capacity (GB) | PFD-23A: 23.3          |
|-----------------------|------------------------|
|                       | PFD-50DLA: 50          |
|                       | PFD-100TLA: 100        |
|                       | PFD-128QLW: 128        |
| Recording Type        |                        |
|                       | PFD-23A: REWRITABLE    |
|                       | PFD-50DLA: REWRITABLE  |
|                       | PFD-100TLA: REWRITABLE |
|                       |                        |
|                       | PFD-128QLW: WRITE-ONCE |

#### Physical Characteristics

| Track pitch (μm)                      | PFD-23A: 0.32<br>PFD-50DLA: 0.32<br>PFD-100TLA: 0.32<br>PFD-128QLW: 0.32     |
|---------------------------------------|------------------------------------------------------------------------------|
| Min. Mark Length (μm)                 | PFD-23A: 0,162<br>PFD-50DLA: 0,149<br>PFD-100TLA: 0,149<br>PFD-128QLW: 0,117 |
| Laser wavelenght-<br>blue violet (nm) | PFD-23A: 405<br>PFD-50DLA: 405<br>PFD-100TLA: 405<br>PFD-128QLW: 405         |
| Writing Transfer Speed<br>(Mbps)      | PFD-23A: 86<br>PFD-50DLA: 86<br>PFD-100TLA: 86                               |

|                    | PFD-128QLW: 144                   |
|--------------------|-----------------------------------|
| Transfer Speed (x) | PFD-23A: 2.4                      |
|                    | PFD-50DLA: 2.4                    |
|                    | PFD-100TLA: 2.4                   |
|                    | PFD-128QLW: 4                     |
| Transfer Speed (x) | PFD-50DLA: 2.4<br>PFD-100TLA: 2.4 |

| Operating Conditions (degrees C)  | -5~55  |  |
|-----------------------------------|--------|--|
| Operating Conditions<br>(% RH)    | 10~90  |  |
| Storage Conditions<br>(degrees C) | -10~55 |  |
| Storage Conditions (% RH)         | 5~90   |  |

| Disc Diameter (mm)   | 120.0 |
|----------------------|-------|
| Cartrige Width (mm)  | 128.6 |
| Cartrige Height (mm) | 130.6 |
| Cartrige Depth (mm)  | 9.1   |

| Cartrige Width (inch)           | 5.125                       |
|---------------------------------|-----------------------------|
| Cartrige Height (inch)          | 5.25                        |
| Cartrige Depth (inch)           | 0.375                       |
| Weight with case (g)            | 183                         |
| Erase/write cycles (times)      | bigger or equal to 1000     |
| Read cycles (times)             | bigger or equal to 1000000  |
| Raw by error rate               | Inferior or equal to 0.0002 |
| Estimated shelf life (years)    | bigger or equal to 50       |
| Estimated archival life (years) | bigger or equal to 50       |

#### Gallery







