

UNI-E2DG8

Security enclosure for SNC-
VB770 camera



Overview

Outdoor camera enclosure with heater/blower and wall-mount bracket

The UNI-E2DG8 is an all-weather security enclosure for use with the Sony SNC-VB770 4K network camera.

Suitable for outdoor use, this vandal resistant fixed camera housing features an integral heater and blower for operation in harsh environments with temperatures ranging from -32°C to 46°C.

Designed to NEMA type 4x standards, the UNI-E2DG8 is IP66 rated for effective moisture and dirt ingress protection, with a sealed clear glass window for superior optical performance.

The housing is constructed from tough molded white polycarbonate, with a powder coated white aluminum wall mount arm and a white pole mounting bracket. Ethernet and power interconnects are provided, with cable interconnects conveniently accessible via a hinged door on the wall-mount arm for ease of installation.

The enclosure also includes a pole-mount adaptor as a standard accessory (straps not included).

Features

Designed for use with SNC-VB770

This outdoor, vandal resistant fixed camera housing is designed for use with the SNC-VB770 4K video network camera.

Integrated blower and heater

The blower runs continuously, providing airflow to keep the camera cool and the window virtually fog-free. The heater automatically activates at 4.4°C and deactivates at 25°C, with a thermal cut-off switch assuring safe heating operation.

Easy installation

Cable interconnects are readily accessible via the hinged door of the wall-mount arm for ease of installation. Ethernet and power interconnects are provided: pre-installed Ethernet cable and power input cabling allows all connections to be performed easily inside the wall-mount arm. Centre-fed cable runs through the wall-mount arm allow a clean, protected install.

Flexible powering options

The enclosure can operate with a power input of 110VAC or 220 VAC 50/60Hz. A camera output of 24VAC or 12 VDC is provided.

Specifications

Mechanical

| | |
|------------------|--|
| Size (H x W x L) | 13.0 x 7.4 x 21.0 inches (330.2 x 187.96 x 533.4 mm) |
|------------------|--|

| | |
|--------|---------------|
| Weight | 4.5 kg/10 lbs |
|--------|---------------|

| | |
|------------------------|---------------|
| Enclosure Construction | Polycarbonate |
|------------------------|---------------|

Wall-Mount Arm

| | |
|--|--|
| Construction | Cast Aluminum |
| Pole-Mount Adaptor Size (H x W x D) | 7.27 x 5.90 x 1.39 inches (184.65 x 149.86 x 533.4 mm) |
| Interior Camera Install Area Available | 3.75 x 5.0 x 13.0 inches (92.25 x 127.0 x 33.2 mm) |
| Maximum Camera and Lens Length | 12.5 inches (317.5mm) |
| Mounting Style | Wall or Pole |
| Window Construction | Glass |

Environmental

| | |
|----------------------------|--------------------------------|
| Operating Temperature | -32°C to 46°C (-25°F to 115°F) |
| Heater Activates at | 4.4°C (40°F) |
| Heater Deactivates at | 25°C (77°F) |
| Blower | Yes (Continuous) |
| IP Rating (Weather Rating) | IP66/NEMA 4X |
| RoHS | Yes |
| REACH | Yes |

| | |
|----------|-----|
| WEEE Yes | Yes |
|----------|-----|

| | |
|----|-----|
| CE | Yes |
|----|-----|

| | |
|---------------|-----|
| UL/cUL Listed | Yes |
|---------------|-----|

Electrical

| | |
|---------------|----------------------------------|
| Input Voltage | 24 VAC/VDC or 110 VAC or 220 VAC |
|---------------|----------------------------------|

| | |
|-------------------|---------------------------------------|
| Power Consumption | 2 amps @ 115 VAC typical at full load |
|-------------------|---------------------------------------|

| | |
|--------------------------|------------------|
| Voltage Output to Camera | 24 VAC or 12 VDC |
|--------------------------|------------------|

Shipping

| | |
|------------|-------------------|
| Box Weight | 6.6 kg (14.5 lbs) |
|------------|-------------------|

| | |
|----------------------------|---|
| Box Dimensions (H x W x D) | 22.0 x 13.0 x 8.0 inches (558.8 x 330.2 x 203.2mm) |
|----------------------------|---|

Gallery

