SONY

VPL-EW348

4,200 lumens WXGA high brightness compact projector with HDBaseT



Overview

Present clear, bright images in larger rooms, plus flexible connectivity and low running costs

The VPL-EW348 projector is ideal for mid-sized and larger classrooms and meeting rooms.

Quiet, compact and powerful, it delivers bright, detail-packed WXGA images with 4,200 colour light output that can be seen clearly even in bright rooms, with Sony's 3LCD technology assuring natural, vivid colours.

The VPL-EW348 is an ideal partner for today's integrated AV/IT environments, expanding your connectivity options with HDBaseT, dual HDMI ports and Direct USB Display connection. A convenient input label function makes life simpler, confirming on screen the name of connected devices.

Add the VPL-EW348 to a network and see presentations from up to four connected PC/Mac computers simultaneously. Slip in an optional Wi-Fi dongle and present directly wirelessly from laptops, phones or tablets. Control the projector remotely with a free app for smartphones and tablets. You don't even need to bring a PC to meetings - just slip in a USB thumb drive and start presenting.

A range of energy-saving features and long-lasting lamp life contribute to low ownership costs. Maintenance is simplified by a new rear lamp access feature.

Features

Bright, clear images with maximum 4,200 lumens colour light output
With a 4,200 lumen maximum light output (in high mode), the VPL-EW348 delivers crisp, bright presentations that can be seen clearly in larger classrooms or meeting rooms. There’s a choice of three brightness modes to suit any environment, from bright daylight to darkened rooms.

3LCD BrightEra™ technology
The efficient 3LCD panel system is enhanced by advanced BrightEra™ technology for impressively bright, consistent, high resolution images with excellent colour accuracy and impressive reliability.

WXGA resolution
WXGA (1280 x 800) 16:10 display resolution gives plenty of crisp detail: ideal for making presentations direct from a laptop, mobile device or DVD player.

Powerful 16W audio
The powerful built-in 16W speaker (mono) lets your audiences hear video soundtracks with no need for additional amplification.

Energy efficient with long-lasting lamp life up to 10,000 hours

High-performance lamp technology offers reduced ownership costs plus reduced maintenance, with a long-lasting lamp replacement time of approx. 10,000 hours (with brightness in low mode).

Advanced energy-saving features
Advanced lamp technology enables a range of energy-saving features. Auto Light Dimming mode saves energy when the projector is left on without being used. Auto Picture Mode automatically adjusts light output to suit the projected scene. Touching a button on the remote mutes the picture temporarily, dramatically reducing power consumption.

Quick go
Don't waste time when you're in a hurry to leave the room: turn off the projector and unplug immediately, with no lengthy waiting for cool-down.

Networked presentations
Project presentations from a networked PC or Mac. Present JPEG, PDF and other files wirelessly from a tablet or smartphone. Up to four users can project PC/Mac images simultaneously, while up to eight users can connect to one projector. The Projector Station for Network Presentation application for Windows/Mac is included. For tablet/smartphone use, an application is provided by Pixelworks, downloaded from the web. For details visit http://PWPresenter.pixelworks.com

Control and management from any networked PC
Projector functions and status can be managed and monitored remotely from any networked PC, using the included Projector Station for Network Control application.

Present wirelessly
Make presentations wirelessly from a portable or handheld device. (Microsoft Windows / Macintosh OS requires Projector Station for Network Presentation application. iOS / Android requires VueMagic application.)

Remote Control app for iOS/Android
Download the free Projector Remote app and control the projector from anywhere in the room with your handheld device, with simple easy-to-read buttons on your phone or tablet screen.

USB media viewer
Slip in a USB drive and display photos, images and graphics with no PC needed.

Supports HDBaseT
Simpler, more cost-effective installation and connectivity with digital transmission of HD video, audio, power and networking/control over a single Ethernet cable.

Dual HDMI inputs
Two HDMI input terminals make it easy to connect HDMI-equipped devices like PCs and media streaming devices.

USB Display function for easy one-cable PC connection
Present pictures and audio* from a connected PC or Mac with just one USB cable - you don't even need to install a software driver.
* There may be a time lag between video and audio. For low-latency applications it is recommended to use projector's line-in or HDMI-in connection.

Customised input naming labels
Define your own input labels like 'BD Player', 'PC' and 'Document Camera', making it easier to see on screen what devices are connected and being used.

Easier maintenance
Lamp access has been shifted to the rear of the projector body, making lamp swaps simpler when the projector is hanging from a ceiling mount.

Quiet operation

Low fan noise ensures discreet, unobtrusive operation in classrooms and meeting rooms.

Specifications

Display System	
Display System	3 LCD system

Display device	
Size of effective display area	0.75” (19 mm) x 3 BrightEra LCD Panel, Aspect ratio: 16:10
Number of pixels	3,072,000 (1280x800 x 3) pixels

Projection lens	
Focus	Manual
Zoom - Powered/Manual	Manual
Zoom - Ratio	Approx. x 1.6
Throw Ratio	1.10:1 to 1.79:1

Light source	
Type	Ultra high pressure mercury lamp
Wattage	225 W type

Recommended lamp replacement time *1	
Lamp mode: High	4000 H
Lamp mode: Standard	6000 H
Lamp mode: Low	10000 H

Filter cleaning / replacement cycle (Max.)	
Filter cleaning / replacement cycle (Max.)	10,000 H

Screen size	
Screen size	30" to 300"(0.76 m to 7.62 m) (measured diagonally)

Light output	
Lamp mode: High	4200 lm
Lamp mode: Standard *2	3200 lm

Light output	
Lamp mode: Low *2	2500 lm

Color light output	
Lamp mode: High	4200 lm
Lamp mode: Standard *2	3200 lm
Lamp mode: Low *2	2500 lm

Contrast ratio (full white / full black) *3	
Contrast ratio (full white / full black)	3700:1

Speaker	
Speaker	16 W (monaural)

Displayable scanning frequency	
Horizontal	15 kHz to 92 kHz
Vertical	48 Hz to 92 Hz

Display resolution	
Computer signal input	Maiximum display resolution: 1600 x 1200 dots *4
Video signal input	NTSC, PAL, SECAM, 480/60i, 576/50i, 480/60p, 575/50p, 720/60p, 720/50p, 1080/60i, 1080/50i, 1080/60p, 1080/50p

Color system	
Color system	NTSC3.58, PAL, SECAM, NTSC4.43, PAL-M, PAL-N, PAL-60

Keystone correction (Max.) *4	
Vertical	+/-20 degrees

OSD languages

OSD languages	27-languages (English, French, German, Italian, Spanish, Portuguese, Japanese, Simplified Chinese, Traditional Chinese, Korean, Russian, Dutch, Norwegian, Swedish, Thai, Arabic,Turkish, Polish, Vietnamese, Farsi, Finnish, Indonesian, Hungary, Greek, Czech, Slovakia, Romania)

INPUT OUTPUT (Computer/Video/Control)

INPUT A	RGB / Y PB PR input connector: Mini D-sub 15-pin (female) Audio input connector: Stereo mini jack
INPUT B	RGB input connector: Mini D-sub 15-pin (female) Audio input connector: Stereo mini jack
INPUT C	HDMI input connector: HDMI 19-pin, HDCP support Audio input connector: HDMI audio support
INPUT D	HDMI input connector: HDMI 19-pin, HDCP support Audio input connector: HDMI audio support
S VIDEO IN	S Video input connector: Mini DIN 4-pin
VIDEO IN	Video input connector: Phono jack
OUTPUT	MONITOR output connector *5: Mini D-sub 15-pin (female) Audio output connector *6: Stereo mini
REMOTE	RS-232C connector: D-sub 9-pin (male)
LAN	RJ45,100BASE-TX (Shared with HDBaseT)
USB	Type-A
USB	Type-B
MICROPHONE IN	Microphone input: Mini Jack

Acoustic noise *5

Lamp mode: Low	29 dB

Operating temperature / Operating humidity

Operating temperature / Operating humidity	0°C to 40°C (32°F to 104°F) / 20-80% (no condensation)

Storage temperature / Storage humidity	
Storage temperature / Storage humidity	-10 °C to +60°C (-4°F to +140°F) / 20% to 80% (no condensation)

Power requirements	
Power requirements	AC 100 V to 240 V, 3.5 A to 1.5 A, 50 Hz / 60 Hz

Power consumption	
AC 100 V to 120 V	Lamp mode: High: 341 W
AC 220 V to 240 V	Lamp mode: High: 329 W

Power Consumption (Standby Mode)	
AC 100 V to 120 V	0.5 W (when “Standby mode” is set to “Low”)
AC 220 V to 240 V	0.5 W (when “Standby mode” is set to “Low”)

Power Consumption (Networked Standby Mode)	
AC 100 V to 120 V	18.5 W (LAN) 14.0 W (optional WLAN module) 19.4 W (All Terminals and Networks Connected) (when "Standby Mode" is set to "Standard")
AC 220 V to 240 V	25.3 W (LAN) 18.5 W (optional WLAN module) 26.3 W (All Terminals and Networks Connected) (when "Standby Mode" is set to "Standard")

Standby Mode/Network Standby Mode Activated	
Standby Mode/Network Standby Mode Activated	Approx. 10 Minutes

Wireless Network(s) On/Off Switch	
Wireless Network(s) On/Off Switch	1) Press the MENU button, then select [Connection/Power] 2) [WLAN Settings] 3) [WLAN Connection] 4) Select On or Off

Heat dissipation	
AC 100 V to 120 V	1163 BTU/h
AC 220 V to 240 V	1122 BTU/h

Dimensions (W x H x D)	
Dimensions (W x H x D) (without protrusions)	Aprox. 365 x 96.2 x 252 mm (14 3/8 X3 25/32 X9 29/32 ”)

Mass	
Mass	Approx. 4.1 kg (9 lb)

Supplied accessories	
Remote commander	RM-PJ8

Optional Accessories	
Optional Lamp	LMP-E221
Wireless LAN module	IFU-WLM3

Notes	
*1	The figures are the expected maintenance time and not guaranteed. They will depend on the environment or how the projector is used
*2	The value are estimate.
*3	The value is average.
*4	Available for the VESA Reduced Blanking signal.
*5	Not available in standby. From INPUT A and INPUT B.
*6	Works as an audio switcher function. Output from a selected channel; not available in standby.
Environmental notice for customers in the USA	Lamp in this product contains mercury. Disposal of these materials may be regulated due to environmental considerations. For disposal or recycling information, please contact your local authorities or see www.sony.com/mercury for additional information.

Information on EU Data Act: Click here to check if your Sony product and/or related service is subject to the EU Data Act.

Gallery











© 2004 - 2026 Sony Corporation. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Features and specifications are subject to change without notice. The values for mass and dimension are approximate. All trademarks are the property of their respective owners.

Export PDF : November 26 2026