

BC-DWX1

Dual battery charger for DWT-B03R wireless transmitter



Overview

Flexible charging options and remote status monitoring

This dual charger is designed for use with the DWT-B03R DWX Series wireless transmitter and NP-BX1 battery pack.

2-way powering allows operation with either AC adaptor* or PoE (Power Over Ethernet).

Battery charging status can be monitored and controlled remotely using Wireless Studio PC software.

Storage charging mode is available for long-term battery storage.

Multiple units can be connected with tie wraps.

*Please note: AC adaptor is not included.

Specifications

Specifications	
Power requirements	When the PoE device is used: 48 V DC When the AC adapter is used: 12 V DC
Current consumption	When the PoE device is used: 260 mA or less When the AC adapter is used: 1.2 A or less
Rated output (Charging)	DC 4.2V, 0.86A (per 1 slot)
LAN Connector	RJ45-type (1) 100BASE-TX : Conforms to IEEE802.3u 10BASE-T : Conforms to IEEE802.3
PoE power reception	Conforms to IEEE802.3af
Operating temperature	0 °C to 40 °C (32 °F to 104 °F) (unit only)
Storage/Transport Temperature	-20 °C to +60 °C (-4 °F to +140 °F)
Supplied accessories	Before Using this Unit (1) CD-ROM (1)
Dimensions (W x H x D)	Approx. 186x71x91 mm

MassApprox. 290 g

Related products

**DWT-B03R**

DWX Series digital wireless
microphone bodypack
transmitter

Gallery

