

PDW-HD1500

XDCAM HD422 Professional Disc recorder up to 50 Mb/s



Overview

The XDCAM production system was first introduced in 2003, offering revolutionary file-based acquisition onto optical Professional Disc. In 2005, XDCAM HD was launched with camcorders and decks recording high definition pictures at up to 35 Mb/s onto the same 23 GB Professional Discs.

At IBC 2007, Sony demonstrated the latest development of products to expand of the XDCAM HD line up - the PDW-700 camcorder and the PDW-HD1500 deck.

The PDW-HD1500 will record and replay XDCAM HD 50 Mb/s 4:2:2 data onto 50 GB Dual-layer Professional Disc. With interfaces including i.LINK and Ethernet, the PDW-HD1500 can operate at the heart of small or large scale file-based networked systems. VTR-like JOG/shuttle operation and video interfaces including HD-SDI and SD-SDI also makes the PDW-HD1500 ideal for operation in more traditional vide-based installations.

The PDW-HD1500 has been designed to increase the appeal of XDCAM HD for high-end applications such as drama, documentary and natural history and for mainstream entertainment programmes that required a prestige quality look.

File-based acquisition onto Professional Disc, with thumbnail and proxy operation will also make the PDW-HD1500 ideal for

networked applications where speed of production is a critical.

Features

High definition recording using MPEG-2 422P@HL compression at 50Mb/s data rate

Support for existing XDCAM HD and XDCAM SD formats

8 channels of digital audio

Dual-layer Disc (50GB) and Single-layer Disc (23.3GB) support

Dual optical pick-up for higher speed file transfer

4.3-inch colour LCD

VTR-like JOG/SHUTTLE operation

TBC control (via front panel and remote)

Compact and lightweight at 6.3kg and half-rack width

AC, DC or battery powered

Built-in up/down converter and 1080/720 cross converter

HD up-conversion from SDI input (recording)

HD/SD conversion and cross conversion output between 1080 and 720 (playback)

Ethernet interface (100Base-T)

i.LINK interface

Specifications

General

| | |
|-----------------------------------|---|
| Power Requirements | AC 100 V to 240 V, 50/60 Hz, DC 12 V |
| Power Consumption | AC: 80 W, DC: 65 W, SAVEMODE (DC): 55 W |
| Operating Temperature | 5°C to 40°C 42°F to 104°F |
| Storage Temperature | -20°C to +60°C -4°F to +140°F |
| Humidity | 25% to 90% (relative humidity) |
| Mass | 6.5 kg 14 lb 5 oz |
| Dimensions (W x H x D) *1 | 210 x 132 x 396 mm (excluding protrusions) 8 3/8 x 5 1/4 x 15 5/8 inches (excluding protrusions) |
| Recording/Playback Format (Video) | MPEG HD422 (CBR, 50 Mbps) MPEG HD: - HQ mode (VBR, maximum bit rate: 35 Mbps) - SP mode (CBR, 25 Mbps) - LP mode (VBR, maximum bit rate: 18 Mbps) *2 MPEG IMX *3 (CBR, 50/40/30 Mbps) DVCAM *3 (CBR, 25 Mbps) |

| | |
|---|--|
| Recording/Playback Format (Audio) | MPEG HD422: 8 ch/24 bits/48 kHz MPEG HD: 4 ch/16 bits/48 kHz MPEG IMX *3 : 4 ch/24 bits/48 kHz or 8 ch/16 bits/48 kHz DVCAM *3 : 4 ch/16 bits/48 kHz |
| Recording/Playback Format (Proxy Video) | MPEG-4 |
| Recording/Playback Format (Proxy Audio) | A-law (8 ch/8 bits/8 kHz) |
| Recording/Playback Time (MPEG HD422) | 50 Mbps: Approx. 95 min (PFD50DLA), Approx. 43 min (PFD23A) |
| Recording/Playback Time (MPEG HD) | 35 Mbps, 4-ch audio: More than 145 min (PFD50DLA), More than 65 min (PFD23A) 35 Mbps, 2-ch audio (playback only): More than 150 min (PFD50DLA), More than 68 min (PFD23A) 25 Mbps, 4-ch audio: Approx. 190 min (PFD50DLA), Approx. 85 min (PFD23A) 25 Mbps, 2-ch audio (playback only): Approx. 200 min (PFD50DLA), Approx. 90 min (PFD23A) |

| | |
|------------------------------------|---|
| | <p>18 Mbps, 4-ch audio (playback only): More than 248 min (PFD50DLA), More than 112 min (PFD23A)</p> <p>18 Mbps, 2-ch audio (playback only): More than 265 min (PFD50DLA), More than 122 min (PFD23A)</p> |
| Recording/Playback Time (MPEG IMX) | <p>50 Mbps: Approx. 100 min (PFD50DLA), Approx. 45 min (PFD23A)</p> <p>40 Mbps: Approx. 120 min (PFD50DLA), Approx. 55 min (PFD23A)</p> <p>30 Mbps: Approx. 150 min (PFD50DLA), Approx. 68 min (PFD23A)</p> <p>Optional PDBK-S1500 hardware key is required for MPEG IMX recording.</p> |
| Recording/Playback Time (DVCAM) | <p>25 Mbps: Approx. 185 min (PFD50DLA), Approx. 85 min (PFD23A) *3</p> |
| Search Speed Range (Shuttle Mode) | -20 times to +20 times normal speed |
| Search Speed Range | |

(Variable Mode) -2 times to +2 times normal speed

Search Speed Range (Jog Mode) -1 time to +1 time normal speed

Search Speed Range (Fast Forward/Reverse) -35/+35 times normal speed

Media Drive

Media Type Professional Disc Drive (x1)

Input/Output

Reference Input BNC (x2) (including loop-through), HD Tri-level sync (0.6 Vp-p/75 Ω/negative) or SD blackburst/composite sync (0.286 Vp-p/75 Ω/negative)

HD-SDI Input BNC (x1) (HD/SD switchable)
 HD-SDI: SMPTE 292M (w/embedded audio)
 SD-SDI: SMPTE 259M (w/embedded audio)

XLR-type 3-pin (female) (x2)

| | |
|-------------------------------|---|
| Analog Audio Input | (channel selectable), +4/0/-3/-6 dBu (selectable), 10 k Ω , balanced |
| Digital Audio Input (AES/EBU) | BNC (x2), 4 ch (2 ch each, 1/2 ch and 3/4 ch), AES-3id-1995 |
| Timecode Input | BNC (x1), SMPTE timecode, 0.5 Vp-p to 18 Vp-p/3.3 k Ω /unbalanced |
| Analog Composite Output | BNC (x2), 1: 1.0 Vp-p/75 Ω /negative, SMPTE 170M 2: 1.0 Vp-p/75 Ω /negative, SMPTE 170M, character On/Off |
| HD-SDI Output | BNC (x2), 1: SMPTE 292M (w/embedded audio) 2: SMPTE 292M (w/embedded audio), character on/off |
| SD-SDI Output | BNC (x2), 1: SMPTE 259M (w/embedded audio) 2: SMPTE 259M (w/embedded audio), character on/off |
| Analog Audio Output | XLR-type 3-pin (male) (x2) (channel selectable), +4/0/-3/-6 dBu (selectable), 600 Ω , Lo-z, balanced |

| | |
|--------------------------------|---|
| Analog Audio Monitor | XLR-type 3-pin (male) (x2), +4 dBu, 600 Ω, Lo-Z, balanced |
| Digital Audio Output (AES/EBU) | BNC (x2), 4 ch (2 ch each, 1/2 ch and 3/4 ch), AES-3id-1995 |
| Headphone Output | JM-60 Stereo phone jack (x1), -13 dBu, 8 Ω, unbalanced |
| Timecode Output | BNC (x1), SMPTE timecode, 1.0 Vp-p/75 Ω/unbalanced |
| Video Control | D-sub 9-pin (female) (x1), EIA RS-423 |
| i.LINK | IEEE 1394 6-pin (x1)* File Access Mode or HDV TS* (1080i/720p) (selectable) *Optional PDBK-201 is required for HDVIN/OUT. |
| Ethernet | RJ-45 (x1) 1000BASE-T: IEEE 802.3ab 100BASE-TX: IEEE 802.3u 10BASE-T: IEEE 802.3 |
| Remote Input (9-pin) | D-sub 9-pin (female) (x1), RS-422A |
| DC Input (12 V) | XLR-type 4-pin (male) (x1) |
| DC Output (12 V) | 4-pin (female) (x1), DC 12 V, 7.5 W |

| | |
|-------------|----------|
| Maintenance | USB (x2) |
|-------------|----------|

| | |
|----------|---|
| AC Input | AC Input (x1), 100 V to 240 V, 50/60Hz |
|----------|---|

Video Performance

| | |
|--------------------|--------------------------------|
| Sampling Frequency | Y: 74.25 MHz, Pb/Pr: 37.125MHz |
|--------------------|--------------------------------|

| | |
|--------------|---------------|
| Quantization | 8 bits/sample |
|--------------|---------------|

| | |
|------------------|-------------------|
| Error Correction | Reed Solomon Code |
|------------------|-------------------|

Processor Adjustment Range

| | |
|-------------|--------------------|
| Video Level | $-\infty$ to +3 dB |
|-------------|--------------------|

| | |
|--------------|--------------------|
| Chroma Level | $-\infty$ to +3 dB |
|--------------|--------------------|

| | |
|--------------------|--|
| Set Up/Black Level | -30 IRE to +30 IRE/-210 mV to +210 mV |
|--------------------|--|

| | |
|--------------|----------------------------|
| Chroma Phase | -30° to $+30^\circ$ |
|--------------|----------------------------|

| | |
|-------------------|--|
| System Sync Phase | $-15 \mu\text{s}$ to $+15 \mu\text{s}$ |
|-------------------|--|

| | |
|-----------------|----------------|
| System SC Phase | 0 ns to 400 ns |
|-----------------|----------------|

Audio Performance

48 kHz

Sampling Frequency

| | |
|--------------------|--|
| Quantization | 24 bits |
| Frequency Response | 20 Hz to 20 kHz +0.5/-1.0 dB (0 dB at 1 kHz) |
| Dynamic Range | More than 90 dB |
| Distortion | Less than 0.05% (at 1 kHz) |
| Headroom | 20/18/16/12 dB (selectable) |

Other Equipment

| | |
|------------------|---------------------------------|
| Built-in Display | 4.3-inch type color LCD monitor |
| Built-in Speaker | Monaural (x1) |

Supplied Accessories

| | |
|----------------------|--|
| Supplied Accessories | Operation manual (1) Installation manual (1) XDCAM Application Software CD-ROM (1) |
|----------------------|--|

Notes

[*1] The values for dimensions are approximate.

Note

[*2] Playback only.

[*3] Optional PDBK-S1500 hardware key is required for DVCAM and MPEG IMX recording.

Gallery

