

BC-U1A

Battery charger/AC adaptor for BP-U90/U60/U60T/U30 Lithium-ion battery



Overview

Charges one BP-U90/U60/U60T/U30 battery

The BC-U1A battery charger charges one compact BP-U90, BP-U60/U60T, BP-U30 Lithium-ion battery at high speed.

Built-in AC adaptor provides 12 V DC power output

The BC-U1A also has 12 V DC power output cable to power a camcorder directly.

Compact design for ease of use

The BC-U1A has a mass of only 340 g (12 oz) and dimensions (W x H x D) of 128 x 45 x 98 mm (5 1/8 x 1 13/16 x 3 7/8 inches).

NOTE: BC-U1A is compliant with safety standard IEC62368-1.

Specifications

General

Power Requirements	AC100V~240V 50/60Hz
--------------------	---------------------

Power consumption	46W
-------------------	-----

DC supply	[36W] 12V / 3.0A
-----------	------------------

Charging Voltage	16.4V
------------------	-------

Dimensions (W x H x D) 128x45x98 (mm)

Mass 340 (g)

Operating [DC supply]-5 °C~+45°C
Temperature [Charge] 0°C~+45°C

Approximate charge times

BP-U90 190 minutes

BP-U60 150 minutes

BP-U30 130 minutes

Supplied Accessories

Supplied Accessories Instruction manual
Warranty Paper

Related products



PXW-FS7M2

4K Super 35mm Exmor CMOS sensor XDCAM camera with Variable ND Filter, E-Mount (Lever Lock), 4K/2K RAW and XAVC recording



PXW-FS5

Grab and Shoot with handheld Super 35



PXW-FS5M2

'Grab and shoot' Super35 handheld camcorder with stunning new creative look, 4K 120fps HFR and HDR, α Mount lens system, Variable ND Filter, 4K/2K RAW



PXW-Z190


4K Handheld Camcorder with all-new 1/3-type 3CMOS with 4K 50p/60p* recording capability, 25x zoom lens and advanced Face Detection AF

and XAVC recording



PXW-FS7

4K Super 35mm
Exmor CMOS sensor
XDCAM camera with α
Mount lens system,
4K/2K RAW and XAVC
recording options



MCX-500

Multi-Camera Live
Producer

Gallery

