

RCP-3500

Remote-control panel for HDC/HSC/HXC series cameras



NETWORKED LIVE

Overview

The RCP-3500 is the successor model for RCP-1500 while keeping the same dimensions and the same basic functions.

The RCP-3500 remote control panel incorporates a brighter LCD display with direct operation switches and a touch panel, visibility improved by higher resolution and brighter LCD device which makes it a remote-control panel that offers both ease of operation and multi-functionality that compares favorably with the MSU. The iris and master black adjustment block employs joystick type control. Up to four units can be mounted in a 19-inch EIA rack.

Features

Touch panel and many direct access switches suitable for various camera operations

This remote control panel is equipped with the control functions required to perform various camera operations enabling the simple and accurate operation of various functions. The operation buttons, adjustment knobs, and other controls are arranged on the panel according to function and frequency of use. Guard frames are provided around buttons that are vital to the operation and setup of cameras to prevent the buttons from being unintentionally operated.

Assignable keys

The RCP-3500 has 9 keys assigned with variety of functions. A spare LED can be also assigned to indicate functioning. All the assigned buttons and LEDs can be listed on the display for easy understanding at a glance.

LAN connection capability

It is possible to connect by LAN cable in addition to connecting using CCA-5 cable. The system can be built using a 1000Base-T LAN connection with PoE support.

Customizable switches

Users can assign any function to the 9 assignable buttons and also make their own favorite menu as well. This is available via SW Customize menu with the categorized items.

HDR operation support

The RCP-3500 supports the HDR related File Names of "All-Setting-File" of HDRC-4000 that can be organized on the RCP's display panel.

The SR Live MetaFile is also supported with HDRC-4000 to link the HDR metadata in addition to SDI connection path.

USB flash drive

The RCP's settings can be saved or loaded via USB flash drive. CAM/CCU/BPU Scene files/Reference files can also be saved, and for the HDRC-4000's HDR Production Converter Unit the All Setting file can be saved.

Direct Scene file control

Easily access Scene file to support various scene setting.

Web UI application

Allows convenient remote operation for RCP initial settings from a remote networked PC with intuitive user interface (UI).*

* Feature available at later date.

Specifications

General

| | |
|------------------------|---|
| Power supply | DC 10.5 V to 17 V (for EXT I/O connector) PoE 36 V to 57 V (IEEE802.3af class 2 compliant) |
| Power consumption | 10 W (including AUX connector output) |
| Operating temperature | 5 °C to 40 °C (41 °F to 104 °F) |
| Storage temperature | -20 °C to 60 °C (-4 °F to 140 °F) |
| Dimensions (W x H x D) | 102 x 310 x 67 mm (4 1/8 x 14 x 2 3/4 inches) (excluding protrusions) |
| Mass | 1.7 kg (3 lb. 12 oz.) |

Input/output connectors

| | |
|---------|---|
| LAN | RJ-45 8-pin (x1) 1000BASE-T, 100BASE-TX, 10BASE-T |
| CCU/CNU | Multi-connector 8-pin, female (x1) |
| AUX | Multi-connector 8-pin, female (x1) |
| EXT I/O | D-sub 9-pin, female (x1) |

Related products



BRC-H800

Premium Full HD PTZ Camera with 12x optical zoom and uncompromising broadcast picture quality



CNA-1

Camera control network adaptor



BRC-X1000

Premium 4K30P PTZ Camera with 12x optical zoom and uncompromising broadcast picture quality



HDC-P31

2/3-type 3-CMOS sensor POV system camera



UHC-8300

1.25-type 8K 3-CMOS sensor portable system camera with 8K 2x HFR capability



HDCU-3100

IP enabled next generation Camera Control Unit



HDCU-3170

IP capable Triax Camera Control Unit



HDCU-3500

IP-ready Camera Control Unit (CCU) for HDC-3500 4K/HD system camera



HDCU-5000

Camera Control Unit (CCU) for HDC-5500 and HDC-3500/3100 series system cameras



HDCU-5500

IP-ready Camera Control Unit (CCU) for HDC-5500 4K/HD system camera



HDC-P50

2/3-type 4K 3-CMOS sensor POV system camera with HD 6x HFR capability



HXC-FB80

4K / HD Camera Control Unit for HXC-FB80 cameras



HXC-P70

Affordable, three 2/3-inch Exmor CMOS sensor, full HD/SD compact system camera with direct optical fibre cable connection



MSU-1000

Master setup unit, multi camera remote control panel for HDC / HSC cameras (horizontal type)



MSU-1500

Master setup unit, multi camera remote control panel for HDC / HSC cameras (vertical type)



BRC-X400

Premium 4K30P IP PTZ Camera with 30x (w/CIZ) zoom and NDI® | HX capability for use in a wide range of environments



MSU-3000

Master setup unit, multi camera remote control panel for system cameras (horizontal type)



MSU-3500

Master setup unit, multi camera remote control panel for system cameras (vertical type)



HDCR-4000

HDR Production Converter Unit



HDC-F5500

Super 35mm 4K CMOS Camera System



HXC-FZ90

2/3-type 4K CMOS sensor portable system camera



HDC-3500V

2/3-type 4K 3-CMOS sensor portable system camera with pre-installed variable ND filter and HD 4x HFR capability



HDC-5500V

2/3-type 4K 3-CMOS sensor portable system camera with pre-installed variable ND filter and 4K 4x HFR capability



CNA-2

Camera Control Network Adapter



BRC-AM7

Premium PTZ Auto Framing Camera with AI Analytics, 4K 60p, 20x optical zoom. High interoperability with other production systems

Gallery



NETWORKED **LIVE**

© 2004 - 2026 Sony Corporation. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Features and specifications are subject to change without notice. The values for mass and dimension are approximate. All trademarks are the property of their respective owners.