

BKM-250TGM



Input adaptor for LMD-3251MT, LMD-3251TC, LMD-2451MT, LMD-2451TC, LMD-2451MD, LMD-2451MC, PVM-2551MD, PVM-2551MC, LMD-1951MD, LMD-1951MC.

This 3G-SDI interface board for LMD-3251MT, LMD-3251TC, LMD-2451MT, LMD-2451TC, LMD-2451MD, LMD-2451MC, PVM-2551MD, PVM-2551MC, LMD-1951MD, LMD-1951MC medical monitors is compliant with the SMPTE 425 standard. It requires only a single SDI cable to transmit up to 10-bit 4:2:2 1080P/60P video signals.

Input

| | |
|-------------------|--|
| SDI Input | <p>BNC (x2) Input impedance: 75 ohms unbalanced Sampling frequency 3G-SDI: Y/Cb/Cr (4:2:2) 148.5 MHz/74.25 MHz/74.25 MHz Y/Cb/Cr (4:4:4) 148.5 MHz/148.5 MHz/148.5 MHz G/B/R 148.5 MHz/148.5 MHz/148.5 MHz HD-SDI: Y/Cb/Cr 74.25 MHz/37.125 MHz/37.125 MHz SD-SDI: Y/Cb/Cr:13.5 MHz/6.75 MHz/6.75 MHz Quantization 3G-SDI: 10 bits/sample, 12 bits/sample HD-SDI: 10 bits/sample SD-SDI: 10 bits/sample</p> |
| Output impedance: | 75-ohms unbalanced |

Output

| | |
|------------|---|
| SDI Output | <p>BNC (x1) (monitor output) *1 Output signal amplitude: 800 mVp-p ±10% Output impedance: 75 ohms unbalanced Transmission distance HD-SDI: 100 m (approx.328 ft) max. *2 SD-SDI: 200 m (approx.656 ft) max. *3</p> |
|------------|---|

Timecode Display

| | |
|--------------------|-------------|
| Available Standard | SMPTE-12M-2 |
| Timecode Type | VITC, LTC |

Audio Level Meter Display

| | |
|---------|---|
| Channel | CH1 to CH8 or CH9 to CH16 |
| Level | -60 dB to -0.01dB |
| Color | -0.01 dB to 0 dB: Red -1.25 dB to -0.01 dB: Orange -20 dB to 1.25 dB: Yellow -60 dB to -20 dB: Green |

General

| | |
|--------------------------------------|---|
| Voltage | +3.3 V, +5 V DC (supplied from the main unit) |
| Power Consumption | Approx. 4.0 W |
| Operating Temperature | 0°C to 35°C (Recommended: 20°C to 30°C) 32°F to 95°F (Recommended: 68°F to 86°F) |
| Operating Humidity | 0% to 90% (no condensation) |
| Storage/Transport Temperature | -20°C to +60°C -4°F to +140°F |
| Storage/Transport Humidity | 0% to 90% |
| Operating/Storage/Transport Pressure | 700 hPa to 1060 hPa |
| Dimensions (W x H x D) *4 | 100 x 20 x 162 mm 4 x 13/16 x 6 1/2 inches |
| Mass | Approx. 270 g Approx. 9.5 oz |
| Supplied Accessories | Operating Instructions (1) |
| *1 | The signal from the monitor output |
| *2 | When using 5C-FB coaxial cables (Fujikura or equivalent). |
| *3 | When using 5C-2V coaxial cables (Fujikura or equivalent). |
| *4 | The values for dimensions are approximate. |

