## SONY

## AC-80MD

AC Adaptor for use with Printer, 3D Camera and IP converter



**Overview** AC-80MD is the AC Adaptor for use with Sony's Printer, 3D Camera and IP converter.

It is compatible with the UP-D711MD Digital Graphic Printer and MCC-3000MT 3D Full HD Medical Video Camera.

Input: AC 100 - 240V, 1.0 - 0.5 Amp, 50/60 Hz Output: DC 24V, 3.3 Amp max. Weight: 350g (AC adaptor only)

### Specifications

#### Specifications

Power requirement	AC 100 V - 240 V, 50/60 Hz
Input current	1.0 A - 0.5 A
Output voltage	DC 24 V
Output current	3.3 A Max
Operating temperature	0 °C to 40 °C (32 °F to 104 °F)

SONY

Operating humidity	20% to 80%
Operating pressure	700 hPa to 1,060 hPa
Storage and transport temperature	–20 °C to +60 °C (–4 °F to +140 °F)
Storage and transport humidity	20% to 90%
Storage and transport pressure	700 hPa to 1,060 hPa
Dimensions	$63 \times 30.5 \times 140$ mm (w/h/d) (2 1/2 $\times$ 1 1/4 $\times$ 5 5/8 inches) Not incl. projecting parts
Mass	350 g (12 oz) (AC adaptor only)
Accessories provided	Instructions for Use (1) Service Contact List (1)

#### Medical Specifications

Protection against electric shock	Class I
Protection against harmful ingress of water	Ordinary

# SONY

Degree of safety in the	Not suitable for use in the
presence of a	presence of a flammable
flammable anesthetic	anesthetic mixture with air or with
mixture with air	oxygen or nitrous oxide
Mode of operation	Continuous



Gallery



© 2004 - 2024 Sony Corporation. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Features and specifications are subject to change without notice. The values for mass and dimension are approximate. All trademarks are the property of their respective owners.

4