

AC-VQ1051D

L series battery AC adaptor/charger



Overview

Power supply/charger compatible with InfoLITHIUM L-series batteries

- Charging time (normal charge / full charge): F570 110 min. / 170 min.; F770 185 min. / 245 min.; F970 285 min. / 345 min.
- Information display shows remaining amount and current battery levels in percentage.
- Relay connections for charging up to two batteries at the same time.
- Includes car charging cord DCC-VQ1

Specifications

Basic Specs

Dimension (Approx.)	W 4-7/8 x H 2-1/8 x D 5-3/8 inches (123 x 53 x 135 mm)
---------------------	---

Weight (Approx.)	14.1 oz (400 g)
------------------	-----------------

Operating Temperature	+32 to +104°F (+0 to +40°C)
-----------------------	-----------------------------

Storage Temperature	-20 to +60°C (-4 to +140°F)
---------------------	-----------------------------

AC Power Requirements

Voltage	100-240V
---------	----------

Frequency	50/60Hz
-----------	---------

DC Power Requirements

Voltage	12/24 V
---------	---------

Power Consumption

Power Consumption	33–43 VA (batt.), 40–53 VA (VCR/camera)
-------------------	---

Adapter

Output Voltage in Operating Mode	DC 8.4 V/2.0 A
----------------------------------	----------------

Charging Specs

Output Voltage in Charging Mode	DC 8.4 V/1.6 A
---------------------------------	----------------

Quick Charge	Quick Charge
--------------	--------------

Intelligent Display (LCD)	Y
---------------------------	---

DC Charge Y

Charging Time

NP-F970 (Full Charge /
Normal Charge) 345 min/285 min

NP-F960 (full
charge/normal
charge) 295 min/235 min

NP-F950 (full
charge/normal
charge) 260 min/200 min

NP-F930 (full
charge/normal
charge) 245 min/185 min

NP-F770 (Full Charge /
Normal Charge) 245 min/185 min

NP-F750 (full
charge/normal
charge) 205 min/145 min

NP-F730 (full
charge/normal
charge) 195 min/135 min

NP-F730H (full

charge/normal charge)	205 min/145 min
-----------------------	-----------------

NP-F570 (Full Charge / Normal Charge)	170 min/110 min
---------------------------------------	-----------------

NP-F550 (full charge/normal charge)	145 min/85 min
-------------------------------------	----------------

NP-F530 (full charge/normal charge)	140 min/80 min
-------------------------------------	----------------

NP-F330 (full charge/normal charge)	115 min/55 min
-------------------------------------	----------------

Eco-info (It is indicated from the high order of priority)

Use of lead-free solder (use 100% in weight)	Lead-free solder is used for soldering
--	--

Reduction and phase-out of halogenated flame retardant (100%)	Halogenated flame retardants are not used in cabinets and in printed wiring boards
---	--

Gallery

