

AC-VQV10

V-series battery AC adaptor/charger



Overview

Power supply/charger compatible with P-, H-, and V-series InfoLITHIUM batteries

High-speed dual charging of P-, H-, and V-series InfoLITHIUM batteries.

Information display shows remaining amount and current battery levels in percent.

Specifications

Basic Specs	
Dimension (Approx.)	W 4 x H 2-3/4 x D 4-3/8 inches (100 x 67 x 111 mm)
Weight (Approx.)	11.7 oz (330 g)
Operating Temperature	0 to +40°C (+32 to +104°F)
Storage Temperature	-20 to +60°C (-4 to +140°F)

AC Power Requirements



Voltage	100-240 V
Frequency	50/60 Hz

Power Consumption

Power Consumption 26 W

Adapter

Output Voltage in Operating Mode

DC OUT 8.4 V/1.7 A

Charging Specs

Output Voltage in Charging Mode

Battery charge terminal 8.4 V/2.2 A

Quick Charge

Quick Charge

Intelligent Display
(LCD)

PC Charge

N

Charging Time

NP-FH100 (full charge/normal charge 190 min/130 min)

SONY

NP-FH70 (full charge/normal charge)	125 min/65 min
NP-FH50 (full charge/normal charge)	115 min/55 min
NP-FP90 (full charge/normal charge)	175 min/115 min
NP-FP50 (full charge/normal charge)	125 min/65 min
NP-FP71 (full charge/normal charge)	140 min/80 min
NP-FV100 (full charge/normal charge)	185 min/125 min
NP-FV70 (full charge/normal charge)	130 min/70 min
NP-FV50 (full charge/normal charge)	115 min/55 min



Eco-info (It is indicated from the high order of priority)

Reduction and phaseout of halogenated flame retardant (100%)

Halogenated flame retardants are not used in cabinets

VOC-free vegetable oil based ink

VOC (volatile organic compound)free vegetable oil based ink is used for printing the cardboard

Remark

Remarks 1: Full charge
Approximate minutes to fully charge an empty battery pack

Remarks 2: Normal
Approximate minutes indicate the time when you charge normally



Gallery

