

## HDCU-5000

Camera Control Unit (CCU) for HDC-5500 and HDC-3500/3100 series system cameras



**NETWORKED LIVE**

### Overview

The HDCU-5000 is a full 19"-rack-size Camera Control Unit (CCU) with dual-transmission capability, offering UHB (Ultra High Bitrate) transmission for the HDC-5500 system camera and 3G transmission for HDC-3500/3100 series system cameras. This choice of transmission options broadens production flexibility for studio, outside broadcast (OB), and sports applications.

The HDCU-5000 is equipped with a range of built-in interfaces including 12G-SDI/3G-SDI/HD-SDI outputs and 12G-SDI/3G-SDI/HD-SDI return inputs.

Providing power to the HDC-5500 camera head, the optical-fiber transmission system maintains uncompromised picture quality over cable runs of up to 13,123.36 feet\*.

\*When supplying power to the camera via optical-fiber cable. Maximum cable length varies according to the camera system configuration, lens type, viewfinder type, size of optical fiber cable and number of cable connectors.

\*1 For more details on the JT-NM Tested program in March 2020 and test results, please go to [https://jt-nm.org/jt-nm\\_tested](https://jt-nm.org/jt-nm_tested).

\*2 For more details on the JT-NM Tested program at IBC 2019 and its test results please see [http://jt-nm.org/jt-nm\\_tested](http://jt-nm.org/jt-nm_tested).

### Features

#### **Versatile built-in interfaces**

The HDCU-5000 features a wide range of built-in interfaces, including 12G-SDI/3G-SDI/HD-SDI outputs and 12G-SDI/3G-SDI/HD-SDI return inputs. The CCU offers four 12G-SDI outputs and a maximum of eight 3G-SDI outputs as standard. Adding the optional HKCU-SDI50 expands this to a maximum of eight 12G-SDI outputs.

#### **LAN interface for network control**

The HDCU-5000 includes a built-in LAN interface (10BASE-T/100BASE-TX). This allows the camera to be controlled over a network, and this interface can also be used for an IP TALLY function.

#### **Ultra-High Bitrate transmission**

The HDCU-5000 supports UHB (Ultra High Bitrate) transmission. This enables 4K 2x slow motion, or simultaneous transmission of two 4K pictures (main camera plus other camera, e.g. a POV picture input to trunk line).

#### **Long-distance transmission and utility out via HDLA**

The CCU's high-power supply allows HDC-5500 series cameras to operate with the HDLA-1500/HDLA-1505/HDLA-1507 HD large lens adaptors over longer distances. HDLA utility out is available with HDCU-5000.

#### **Extensive expansion options**

The HDCU-5000 offers four types of interface expansion option. The HKCU-SDI50 provides four additional 12G-SDI interfaces. The HKCU-SFP50 provides an ST 2110 IP interface (including IP intercom function). The HKCU-SM50 provide a single-mode fiber connection capability between the camera and CCU. The HKCU-REC50 adds a CCU internal recording capability, allowing up to four hours recording time at 4K XAVC-I C300.

### Gigabit Ethernet trunk line

The HDCU-5000 CCU features a single channel trunk line (1Gb Ethernet) to support easy data transmission.

### Multi-format functionality

The HDCU-5000 offers multi-format support for 4K up to 2x, HD HFR up to 8x, progressive-segmented-frame format, 1080-4:4:4-RGB (@23.98PsF, 24PsF, 25PsF, 29.97PsF).

### Recording and real-time network transfer

Adding the HKCU-REC50 internal recording option allows the HDCU-5000 CCU to record the camera's live feed (up to 4 hours recording time at 4K XAVC-I C300). Footage can be transferred in real time to a connected USB solid state drive or NAS (Network Attached Storage) device while recording takes place. As soon as shooting is finished, the file is immediately available on the attached storage device.

## Specifications

### General

Power Requirements	100/120/220 V to 240 V AC, 50/60 Hz (For details about switching the voltage, contact a Sony service or sales representative.)
Current consumption	7 A (max.)
Operating temperature	5 °C to 40 °C (41 °F to 104 °F)
Storage temperature	-20 °C to +60 °C (-4 °F to +140 °F)
Weight	Approx. 19.5 kg (43 lb)

### Input/Output Connectors

CAMERA	Optical fiber connector (2)
INTERCOM/TALLY/IO PORT	D-sub 50-pin connector (M2.6) (1) INTERCOM (PROD/ENG), 4 W: 0 dBu, RTS: 0 dBu, CC: -14 dBu PGM, 3 systems, 0 dBu/-20 dBu TALLY (R, G, Y) FLAG
RCP / CNU	8-pin multi-connector (x1)
TRUNK	12-pin(x1)
LAN-COM	8-pin (x1)
NETWORK TRUNK	8-pin (x1)

<p>UHD SDI</p>	<p>UHD-SDI A, B:                      12G/6G/3G/HD-SDI OUTPUT                      BNC type (2)                      12G-SDI: SMPTE ST2082, 0.8 Vp-p, 75 ohms,                      11.88 Gbps/11.868 Gbps                      6G-SDI: SMPTE ST2081, 0.8 Vp-p, 75 ohms,                      5.940 Gbps/5.934 Gbps                      3G-SDI: SMPTE ST424/425 Level-A/B, 0.8 Vp-p,                      75 ohms, 2.970 Gbps/2.967 Gbps                      HD-SDI: SMPTE ST292, 0.8 Vp-p, 75 ohms,                      1.485 Gbps/1.4835 Gbps</p> <p>UHD-SDI C, D:                      12G/6G/3G/HD-SDI I/O                      BNC type (2)                      12G-SDI: SMPTE ST2082, 0.8 Vp-p, 75 ohms,                      11.88 Gbps/11.868 Gbps                      6G-SDI: SMPTE ST2081, 0.8 Vp-p, 75 ohms,                      5.940 Gbps/5.934 Gbps                      3G-SDI: SMPTE ST424/425 Level-A/B, 0.8 Vp-p,                      75 ohms, 2.970 Gbps/2.967 Gbps                      HD-SDI: SMPTE ST292, 0.8 Vp-p, 75 ohms,                      1.485 Gbps/1.4835 Gbps</p>
<p>SDI OUT</p>	<p>SDI OUT 1 to 4:                      3G/HD/SD-SDI OUTPUT                      BNC type (4)                      3G-SDI: SMPTE ST424/425 Level-A/B, 0.8 Vp-p,                      75 ohms, 2.970 Gbps/2.967 Gbps                      HD-SDI: SMPTE ST292, 0.8 Vp-p, 75 ohms,                      1.485 Gbps/1.4835 Gbps                      SD-SDI: SMPTE 259M, 0.8 Vp-p, 75 ohms,                      270 Mbps</p>
<p>SDI I/O</p>	<p>SDI I/O 1 to 4:                      3G/HD/SD-SDI I/O                      BNC type (4)                      3G-SDI: SMPTE ST424/425 Level-A/B, 0.8 Vp-p,                      75 ohms, 2.970 Gbps/2.967 Gbps                      HD-SDI: SMPTE ST292, 0.8 Vp-p, 75 ohms,                      1.485 Gbps/1.4835 Gbps                      SD-SDI: SMPTE 259M, 0.8 Vp-p, 75 ohms,                      270 Mbps</p>
<p>SDI RET</p>	<p>SDI RET 1 to 4:                      BNC type (4)                      3G-SDI: SMPTE ST424/425,                      2.970 Gbps/2.967 Gbps                      HD-SDI: SMPTE ST292,                      1.485 Gbps/1.4835 Gbps                      SD-SDI: SMPTE 259M, 270 Mbps</p>
<p>REFERENCE IN/OUT</p>	<p>BNC type (2), loop-through output,                      HD: 3-level sync, 0.6 Vp-p, 75 Ω,                      SD: 2-level sync, 0.3 Vp-p, 75 Ω</p>

## Input/Output Connectors

PROMPTER 1 PROMPTER 2/VBS-RET	BNC type (2), terminated internally at 75 ohms during 2CH mode, analog signal, 1.0 Vp-p, 75 ohms
AUDIO OUT	AUDIO OUT CH1, CH2: XLR 3-pin, male (2), 0 dBu/-20 dBu/ +4 dBu
CHARACTER / SYNC	VBS: 1 Vp-p, 75 Ω, HD: 3-level sync, 0.6 Vp-p, 75 Ω, SD: 2-level sync, 0.3 Vp-p, 75 Ω
AES/EBU	AES/EBU: 0.5 Vp-p, 75 Ω
AC IN	100/120/220 V to 240 V AC (1) (For details about switching the voltage, contact a Sony service or sales representative.)

## Supplied Accessories

Supplied accessories	Number plates (1 set) Before Using this Unit (1) Operating Instructions (CD-ROM) (1)
----------------------	--

## Related products



### HDC-1700

Multi format HD portable system camera



### HDC-3100

Three 2/3-inch CMOS sensors portable system camera for fiber operation



### HDC-3500

Three 2/3-inch 4K CMOS sensors portable system camera for fiber operation



### HDC-5500

High performance three 2/3-inch 4K CMOS sensor portable system camera with direct 4K output



### PWA-RCT1

Recording control software for PWS-4500, HKCU-REC55 and HKCU-REC50



### HKCU-REC50

Recording option for HDCU-5000



### HZCU-UHDR50

4K Recording License for HDCU-5000/5500/3500



### PWAL-RCT50

CCU recording control option for PWA-RCT1



### HZCU-DHR50

DNxHD Codec License for HDCU-5000, HDCU-5500 and HDCU-3500 camera control units



### RCP-3500

Remote-control panel for HDC/HSC/HXC series cameras



### RCP-3501

Remote-control panel for HDC/HSC/HXC series cameras



### MSU-3000

Master setup unit, multi-camera remote control panel for system cameras (horizontal type)



### MSU-3500

Master setup unit, multi-camera remote control panel for system cameras (vertical type)

### HDCE-TX50

IP camera extension adaptor for remote live production (transmitter)

### HDCE-RX50

IP CCU extension adaptor for remote live production (receiver)


### HDC-F5500

Super 35-mm 4K CMOS Camera System



### HKC-VND50

Variable ND filter unit



### HKCU-UHF50

4K 4x processor board for HDCU-5000



### CNA-2

Camera Control Network Adapter

## Gallery



© 2004 - 2026 Sony Corporation. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Features and specifications are subject to change without notice. The values for mass and dimension are approximate. All trademarks are the property of their respective owners.