

## RM-B170

Affordable handheld remote control unit for Sony studio cameras and camcorders



### Overview

The RM-B170 remote control unit is the successor to the RM-B150. It provides an even more affordable solution for basic remote camera operations, with added features, including remote control of media and the operation of non-linear media clips. It can be directly connected to a camera or camcorder as a portable-type remote control unit or it can be connected to a CCU for use as a simple remote control panel. The RM-B170 can control a camera from a distance of up to 100 m (328 ft) when connected directly to the camera.

For use with the following Sony cameras:

HDCAM camcorders: HDW-700A, HDW-650, HDW-750, HDW-F900/H/R

XDCAM HD422 Professional Disc camcorders: PDW-680, PDW-700, PDW-F800

XDCAM HD422 Memory camcorders: PMW-300, PMW-400, PMW-500

XDCAM EX Memory camcorders: PMW-EX3, PMW-320, PMW-350, PMW-F3

XDCAM Memory camcorders: PXW-Z750, PXW-Z450, PXW-X400, PXW-X500, PXW-X320

Digital Cinematography & 4K XAVC: F23, F35, F65, PMW-F5, PMW-F55

Digital Cinema Cameras: VENICE, VENICE 2

Studio cameras: BVP-950A, BVP-750A, BVP-550/570, HDC & HXC series

## Features

### **Media and recorded files access and viewing at a distance**

As well as camera painting adjustment, the unit can control media inserted in the recorder connected to camera or a camcorder. It also supports the operation of clips of non-linear media.

### **Monitor output or 'control only'**

The unit is supplied with a 10-m interconnect 8-pin remote cable, which provides an analog composite output for a picture monitor for all camcorder series (down-converter must be enabled on HD models).

### **May be used in applications or in place of RCP-700 series remote control panels**

The RM-B170 uses the new studio camera command system and may be used in applications or in place of RCP-700 series remote control panels.

### **Control of automatic adjustment functions**

The RM-B170 can perform automatic black/white adjustment of the camera.

### **Control of the ECS/ shutter function**

The Extended Clear Scan (ECS) and electronic shutter functions of the camera can be turned on and off from the unit. It is also possible to adjust the ECS frequency and shutter speed.

### **Control of the Slow Shutter function**

The RM - B170 can set the number of accumulated frames for a camera equipped with the SLS (Slow Shutter) function.

### **Parallel operation with another control panel**

When the unit is connected to a camera via a camera control unit, the camera can be concurrently controlled from this unit and another remote control panel, such as the MSU-1000/1500-series master setup unit or RCP-1000/1500-series remote control panel. This makes it an affordable solution for multi-camera shoots.\*

\*Some CCU model doesn't support multiple control.

### **Assignable buttons**

Various functions can be assigned to two buttons, which allows journalists live logging (shot markers) or camera function activation.

### **High brightness buttons**

The operations buttons and controls on the front panel of the unit include buttons with Superluminescence LEDs, making them easy to identify in a low and high light environment and indicating the operation status by flashing or lighting. The brightness of the indicators can be adjusted.

### **Guard to prevent unintended operation**

A guard is in place around the buttons where operation by mistake might seriously affect camera operation or setups.

### **GPI interface**

External GPI Input/output (D Sub 9 pin connector) support Red and Green Tally outputs, a 12V DC input and a spare input for future use.

Related products



#### **HDC-4300L**

4K and HFR Live



#### **HXC-FB80**

Three 2/3-inch Exmor™ CMOS sensor

Camera System

HD color studio  
camera

## Gallery

