

VPL-GTZ240

4K SXRD compact laser projector with 2000-lumens output and accurate reproduction of high-speed motion



Overview

Smooth, precise moving images with 4K clarity and special functions for visual simulation.

For advanced simulation applications, the VPL-GTZ240 laser projector delivers high-contrast 4K images with 2,000 lumens light output and smooth, ultra-responsive reproduction of fast-moving action.

The long-lasting laser light source is combined with 4K SXRD panel technology to deliver bright, crisply detailed native 4K images (4096 x 2160) with more than four times the resolution of Full HD. Picture quality is further enhanced by Reality Creation upscaling, plus configurable support for HDR (High Dynamic range) and high frame rates to take full advantage of today's premium 4K content — and tomorrow's.

The VPL-GTZ240 has two types of black frame insertion modes to reduce motion blur and smear. The low transport delay contributes to an extremely responsive performance in fast-motion simulator applications.

The VPL-GTZ240 is particularly suitable for demanding multi-projection applications in 2D or 3D, with consistently homogeneous brightness.

The highly efficient laser light source is rated for a nominal 20,000 hours* for virtually zero maintenance without the need for any lamp exchanges.

*Depends on usage and environment.

Features

Native 4K clarity with more than four times the resolution of Full HD

Advanced SXRD panel technology featured in Sony's digital cinema projectors delivers native 4K (4096 x 2160) resolution images, with no artificial pixel enhancement. Every detail is wonderfully clear and natural, without jagged edges or visible pixels.

Pre-adjusted brightness and color temperature for multi-projection

The brightness and color temperature of the VPL-GTZ240 has been pre-adjusted in order to reduce the adjustment time for multi-projection.

Super high contrast ratio

The advance optical engine reduces internal light leakage, for spectacularly high contrast images with huge amounts of finely-rendered picture detail in dark shots.

Supports HDR

Take full advantage of the latest content produced with High Dynamic Range for sharp

contrast and more accurate detail, from searing highlights to richly detailed dark scenes.

Reality Creation upscaling

Lower resolution input signals are accurately upscaled to 4K pixel resolution by Sony's advanced Reality Creation engine: you won't see any individual pixels - just beautifully natural 4K images.

Long-lasting laser light source

Thanks to the highly efficient and reliable laser light source, users can benefit from startlingly clear 4K pictures, plus up to 20,000 hours* uninterrupted operation with no lamp replacement — far longer than conventional lamp-based projectors.

*Depends on usage and environment.

Low transport delay

Enjoy responsive, lag-free performance with an extremely low transport delay; ideal for fast-moving content.

Quick start

Don't lose time - laser light source starts instantly, allowing you to start projecting in moments without lengthy lamp warm-up time.

Motionflow for smoother 4K images

Motionflow ensures smoother, less blurry on-screen images.

Advanced motion blur reduction

A choice of black insertion ratio modes allows effective reduction of image blur and smear.

Industry standard RF 3D compatible

The projector's built-in RF transmitter synchronizes with any RF 3D glasses for wider coverage and greater stability, with no need for an external transmitter.

Whisper quiet operation

Extra-low noise fan with a one-way air flow ensures extra-quiet operation for minimized audience disruption. High altitude mode adjusts fan rate for efficient operation at altitudes above 1500 m.

Specifications

Display System	
Display System	4K SXRD panel, projection system
Display device	
Size of effective display area	0.74" x 3
Number of pixels	26,542,080 (4096 x 2160 x 3) pixels
Projection lens*1	
Focus	Powered
Zoom	Powered (Approx. x2.15: VPLL-Z7013) (Approx. x1.34: VPLL-Z7008)

Lens Shift	Powered Vertical: +/-80%, Horizontal: +/-31% : VPLL-Z7013 Vertical: +/-50%, Horizontal: +/-18% : VPLL-Z7008
------------	---

Light Source

Light Source	Laser diode
--------------	-------------

Light output

Light output	2,000 lm
--------------	----------

Color light output

Color light output	2,000 lm
--------------------	----------

Contrast ratio

Contrast ratio	16,000:1 *2 (native contrast)
----------------	-------------------------------

Acceptable signals

Acceptable signals	480/60p, 576/50p, 720/60p, 720/50p, 1080/60i, 1080/50i, 1080/60p, 1080/50p, 1080/24p, 3840 x 2160/24p, 3840 x 2160/25p, 3840 x 2160/30p, 3840 x 2160/50p, 3840 x 2160/60p, 4096 x 2160/24p, 4096 x 2160/25p, 4096 x 2160/30p, 4096 x 2160/50p, 4096 x 2160/60p
--------------------	--

Color bit depth

Color bit depth	Up to 12 bit
-----------------	--------------

INPUT OUTPUT (Computer/Video/ Control)

HDMI1 / HDMI2 *3	Digital (RGB/Y Pb/Cb Pr/Cr)
TRIGGER	Mini jack, DC 12V Max.100 mA
REMOTE	RS-232C, D-sub 9-pin (male)
LAN	RJ45, 10BASE-T/100BASE-TX
IR IN	Mini jack
USB	DC 5V, Max. 500 mA

OSD languages

OSD languages	18-languages (English, Dutch, French, Italian, German, Spanish, Portuguese, Turkish, Russian, Swedish, Norwegian, Japanese, Simplified Chinese, Traditional Chinese, Korean, Thai, Arabic, Polish)
---------------	--

Acoustic noise

Acoustic noise	39 dB*2
----------------	---------

Operating temperature / Operating humidity

Operating temperature / Operating humidity	5°C to 40°C (41°F to +104°F)/20% to 80% (no condensation)
--	---

Storage temperature / Storage humidity

Storage temperature / Storage humidity	-10°C to + 60°C (14°F to +140°F)/20% to 80% (no condensation)
--	---

Power requirements

Power requirements	AC 100 V to 240 V, 4.9 A to 2.2 A, 50/60Hz
--------------------	--

Power consumption

Power consumption	MAX. 490 W
-------------------	------------

Power consumption (Standby Mode)	0.4 W (When "Remote Start" is set to "Off")
----------------------------------	---

Power consumption (Networked Standby Mode)	1.0 W (LAN) (when "Remote Start" is set to "On"). When a LAN terminal is not connected, it becomes a low power consumption mode (0.5 W).
--	--

Standby Mode / Networked Standby Mode Activated

Standby Mode / Networked Standby Mode Activated	After about 10 Minutes
---	------------------------

Heat dissipation

Heat dissipation	1671 BTU/h
------------------	------------

3D

3D capability	Yes
---------------	-----

3D emitter	Built-in RF emitter
------------	---------------------

3D glasses	Consult with qualified Sony personnel
Dimensions	
Dimensions (W x H x D)	560 x 223 x 496 mm (22 1/16 x 8 25/32 x 19 17/32 in) (without protrusions)
Mass	
Mass	Approx. 19.5 kg/43 lb (without lens)
Supplied accessories	
Supplied accessories	RM-PJ29 Remote Commander (1), Size AA (R6) manganese batteries (2), AC power cord (1), Operating instructions (CD-ROM) (1) Safety regulations (5)
Optional accessories	VPLL-Z7008, VPLL-Z7013
Notes	
*1	The lenses are optional accessories
*2	This value is typical and it depends on the projector setting condition and usage environment
*3	Both HDMI inputs are compatible with HDCP 2.2.

Gallery

